

## ToLEDo Retro G80

ToLEDo RT G80 V3 CL 470LM 827 B22 SL

0027171



### Product features

- Perfect for decorative and general lighting applications and creates a warm ambiance similar to traditional lamps
- Same look, size and functionality as incandescent lamps
- Omni-directional light distribution
- First lamp of its type to achieve A++ rating - up to 118 lm/W
- Suitable for replacement of 40W incandescent lamps
- Gives same sparkling light effect as incandescent lamp
- 90% energy saving
- Dimensionally identical to incandescent lamps - fits all fixtures
- Environment friendly - no mercury and lower CO2 emissions
- Color temperature - 2700K Homelight
- Diameter - 80mm



## PRODUCT OVERVIEW

IPC Code	0027171
Product name	ToLEDo RT G80 V3 CL 470LM 827 B22 SL
Technology	LED
Watt (Rated) (W)	4.5
Cap/Base	B22
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Certifications	EUTIE103
ETIM Class	EC001959
E-number SE	8295072
Luminous flux (lm)	470
Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Colour Consistency (SDCM)	6
Beam Angle (°)	300
Wattage (W)	4.5
Product Voltage (V)	230
Average life (Nominal) (h)	15000
Product EAN number	5410288271712

## DATA TABLE

### General data

IPC Code	0027171
Product name	ToLEDo RT G80 V3 CL 470LM 827 B22 SL
Technology	LED
Watt (Rated) (W)	4.5
Cap/Base	B22
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Operating temperature rated (°C)	25
Certifications	EUTIE103

## ToLEDo Retro G80

*ToLEDo RT G80 V3 CL 470LM 827 B22 SL*

0027171

ETIM Class	EC001959
E-number SE	8295072

### Optical data

Luminous flux (lm)	470
Luminous flux (Rated) (lm)	470
Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Colour Consistency (SDCM)	6
Adjustable chromaticity	N
Beam Angle (°)	300
Beam angle (Rated) (°)	300
Lumen maintenance at end of nominal life (%)	70

### Electrical data

Wattage (W)	4.5
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	1
Product Voltage (V)	230
Lamp power factor	0.5
No. Of switching cycles before premature failures	50000
Lamp Energy Label (class)	A++
kWh per 1000 hours burning time	5
Nominal Frequency (Hz)	50/60Hz

### Lifetime data

Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

### Physical data

Nominal Product Length (mm)	120
Nominal Product Diameter (mm)	80
Weight (kg)	0.043

### Packaging

Single packaging type	Carton
Product EAN number	5410288271712
Packaging single length / height (cm)	13.0
Packaging single width (cm)	8.5
Packaging single depth (cm)	8.5
DUN14 (inner)	25410288271716
Units per inner package	6
Packaging inner length / height (cm)	26.8
Packaging inner width (cm)	17.8
Packaging inner depth (cm)	14.5

## ToLEDo Retro G80

ToLEDo RT G80 V3 CL 470LM 827 B22 SL

0027171

DUN14 (outer)	15410288271719
Units per outer package	60
Packaging outer length / height (cm)	91.6
Packaging outer width (cm)	28.2
Packaging outer depth (cm)	31.9

### Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Intended purpose	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

