

ToLEDo Superia Tube T5

TOLEDO SUPERIA T5 HE 4FT 2200LM 830
0029504



Product features

- 60,000 hours average rated lifetime (L70 F50) • Last 3 times longer than 28W 1149mm fluorescent tri-phosphor T5 lamp. • High switching cycles - 200,000X • High lumen efficacy -138lm/W • Omni-directional light distribution and wide beam angle • Minimum and maximum operating temperature: - 20°C to 50°C • Glass construction and polycarbonate end-caps • Not suitable for direct mains (AC 220-240V) or magnetic/ CCG ballast • Works only with compatible electronic ballasts. • Ideal for factories, parking lots, supermarkets, department stores, schools and offices.



PRODUCT OVERVIEW

IPC Code	0029504
Product name	TOLEDO SUPERIA T5 HE 4FT 2200LM 830
Technology	LED
Watt (Rated) (W)	16
General application	Office,Hospitality,Logistics & Industry,Retail,Residential & Consumer,Museums & Galleries,Education,
Certifications	EUERL010
ETIM Class	EC001959
E-number FI	4740601
E-number SE	8293574
Fixture luminous flux (lm)	RPLA01 : Royalty LED Lamp Single Colour
Luminous flux (lm)	2200
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Wattage (W)	16
Product Voltage (V)	80
Average life (Nominal) (h)	60000
Product EAN number	5410288295046

DATA TABLE

General data

IPC Code	0029504
Product name	TOLEDO SUPERIA T5 HE 4FT 2200LM 830
Technology	LED
Watt (Rated) (W)	16
General application	Office,Hospitality,Logistics & Industry,Retail,Residential & Consumer,Museums & Galleries,Education,
Operating temperature rated (°C)	25
Certifications	EUERL010
ETIM Class	EC001959
E-number FI	4740601
E-number SE	8293574

ToLEDo Superia Tube T5

TOLEDO SUPERIA T5 HE 4FT 2200LM 830
0029504

Optical data

Fixture luminous flux (lm)	RPLA01 : Royalty LED Lamp Single Colour
Luminous flux (lm)	2200
Luminous flux (Rated) (lm)	2200
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Beam angle (Rated) (°)	220
Lumen maintenance at end of nominal life (%)	70

Electrical data

Wattage (W)	16
Watt (Rated) - High frequency (W)	16
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	<2
Current (A)	0.24
Product Voltage (V)	80
Lamp power factor	0.89
No. Of switching cycles before premature failures	200000
Lamp Energy Label (class)	A++
kWh per 1000 hours burning time	18

Lifetime data

Average life (Nominal) (h)	60000
Average life (Rated) (h)	60000

Physical data

Nominal Product Diameter (mm)	1149
Weight (kg)	0.148

Packaging

Single packaging type	Carton
Product EAN number	5410288295046
Packaging single length / height (cm)	116.5
Packaging single width (cm)	1.8
Packaging single depth (cm)	1.8
DUN14 (outer)	15410288295043
Units per outer package	10
Packaging outer length / height (cm)	122.0
Packaging outer width (cm)	15.5
Packaging outer depth (cm)	8.0

Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Suitable for household illumination	Yes

ToLEDo Superia Tube T5

TOLEDO SUPERIA T5 HE 4FT 2200LM 830
0029504

Safety message

Suitable for approved transf./dimmers

TECHNICAL DRAWINGS

