

## ToLEDo Superia Tube T5

TOLEDO SUPERIA T5 HE 5FT 2800LM 840  
0029511



### Product features

- 60,000 hours average rated lifetime (L70 F50) • Last 3 times longer than 35W 1449mm fluorescent tri-phosphor T5 lamp. • High switching cycles - 200,000X • High lumen efficacy -151lm/W • Omni-directional light distribution and wide beam angle • Minimum and maximum operating temperature: - 20°C to 50°C • Glass construction and polycarbonate end-caps • Not suitable for direct mains (AC 220-240V) or magnetic/ CCG ballast • Works only with compatible electronic ballasts. • Ideal for factories, parking lots, supermarkets, department stores, schools and offices.



## PRODUCT OVERVIEW

IPC Code	0029511
Product name	TOLEDO SUPERIA T5 HE 5FT 2800LM 840
Technology	LED
Watt (Rated) (W)	18.5
General application	Office,Hospitality,Retail,Logistics & Industry,Education,Residential & Consumer,Museums & Galleries,
Certifications	EUERL010
ETIM Class	EC001959
E-number FI	4740608
E-number SE	8293581
Fixture luminous flux (lm)	RPLA01 : Royalty LED Lamp Single Colour
Luminous flux (lm)	2800
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Wattage (W)	18.5
Product Voltage (V)	80
Average life (Nominal) (h)	60000
Product EAN number	5410288295114

## DATA TABLE

### General data

IPC Code	0029511
Product name	TOLEDO SUPERIA T5 HE 5FT 2800LM 840
Technology	LED
Watt (Rated) (W)	18.5
General application	Office,Hospitality,Retail,Logistics & Industry,Education,Residential & Consumer,Museums & Galleries,
Operating temperature rated (°C)	25
Certifications	EUERL010
ETIM Class	EC001959
E-number FI	4740608

## ToLEDo Superia Tube T5

TOLEDO SUPERIA T5 HE 5FT 2800LM 840  
0029511

E-number SE 8293581

### Optical data

Fixture luminous flux (lm)	RPLA01 : Royalty LED Lamp Single Colour
Luminous flux (lm)	2800
Luminous flux (Rated) (lm)	2800
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Beam angle (Rated) (°)	220
Lumen maintenance at end of nominal life (%)	70

### Electrical data

Wattage (W)	18.5
Watt (Rated) - High frequency (W)	18.5
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	<2
Current (A)	0.24
Product Voltage (V)	80
Lamp power factor	0.92
No. Of switching cycles before premature failures	200000
Lamp Energy Label (class)	A++
kWh per 1000 hours burning time	21

### Lifetime data

Average life (Nominal) (h)	60000
Average life (Rated) (h)	60000

### Physical data

Nominal Product Diameter (mm)	1449
Weight (kg)	0.174

### Packaging

Single packaging type	Carton
Product EAN number	5410288295114
Packaging single length / height (cm)	146.5
Packaging single width (cm)	1.8
Packaging single depth (cm)	1.8
DUN14 (outer)	15410288295111
Units per outer package	10
Packaging outer length / height (cm)	152.0
Packaging outer width (cm)	15.5
Packaging outer depth (cm)	8.0

### Safety data

Breakage cleaning instructions	Not applicable
--------------------------------	----------------

## ToLEDo Superia Tube T5

TOLEDO SUPERIA T5 HE 5FT 2800LM 840  
0029511

Special purpose lamp	No
Suitable for household illumination	Yes
Safety message	Suitable for totally enclosed fixture

