ToLEDo Superia Tube T5

TOLEDO SUPERIA T5 HE 5FT 2800LM 865

0029512



Product features

- • 60,000 hours average rated lifetime (L70 F50) • Last 3 times longer than 35W 1449mm fluorescent tri-phosphor T5 lamp. • High switching cycles - 200,000X • High lumen efficacy -151lm/W • Omni-directional light distribution and wide beam angle • Minimum and maximum operating temperature: -20°C to 50°C • Glass construction and polycarbonate end-caps • Not suitable for direct mains (AC 220-240V) or magnetic/ CCG ballast • Works only with compatible electronic ballasts. • Ideal for factories, parking lots, supermarkets, department stores, schools and offices.

PRODUCT OVERVIEW

IPC Code	0029512
Product name	TOLEDO SUPERIA T5 HE 5FT 2800LM 865
Technology	LED
Watt (Rated) (W)	18.5
General application	Office,Hospitality,Retail,Logistics & Industry,Education,Residential & Consumer,Museums & Galleries,
Certifications	EUERL010
ETIM Class	EC001959
E-number FI	4740609
E-number SE	8293582
Fixture luminous flux (lm)	RPLA01 : Royalty LED Lamp Single Colour
Luminous flux (lm)	2800
Colour temperature (K)	6500
Light colour	Daylight
CRI (Ra)	80
Wattage (W)	18.5
Product Voltage (V)	80
Average life (Nominal) (h)	60000
Product EAN number	5410288295121

DATA TABLE

General data

IPC Code	0029512
Product name	TOLEDO SUPERIA T5 HE 5FT 2800LM 865
Technology	LED
Watt (Rated) (W)	18.5
General application	Office,Hospitality,Retail,Logistics & Industry,Education,Residential & Consumer,Museums & Galleries,
Operating temperature rated (°C)	25
Certifications	EUERL010
ETIM Class	EC001959
E-number FI	4740609

© Feilo Sylvania | Date Printed: 19 Dec 2018

ToLEDo Superia Tube T5

TOLEDO SUPERIA T5 HE 5FT 2800LM 865

0029512

E-number SE	8293582

Optical data

Fixture luminous flux (lm)	RPLA01 : Royalty LED Lamp Single Colour
Luminous flux (lm)	2800
Luminous flux (Rated) (lm)	2800
Colour temperature (K)	6500
Light colour	Daylight
CRI (Ra)	80
Beam angle (Rated) (°)	220
Lumen maintenance at end of nominal life (%)	70

Electrical data

Wattage (W)	18.5
Watt (Rated) - High frequency (W)	18.5
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	<2
Current (A)	0.24
Product Voltage (V)	80
Lamp power factor	0.92
No. Of switching cycles before premature failures	200000
Lamp Energy Label (class)	A++
kWh per 1000 hours burning time	21

Lifetime data

Average life (Nominal) (h)	60000
Average life (Rated) (h)	60000

Physical data

Nominal Product Diameter (mm)	1449
Weight (kg)	0.174

Packaging

Single packaging type	Carton
Product EAN number	5410288295121
Packaging single length / height (cm)	146.5
Packaging single width (cm)	1.8
Packaging single depth (cm)	1.8
DUN14 (outer)	15410288295128
Units per outer package	10
Packaging outer length / height (cm)	152.0
Packaging outer width (cm)	15.5
Packaging outer depth (cm)	8.0

Safety data

Breakage cleaning instructions	Not applicable


© Feilo Sylvania | Date Printed: 19 Dec 2018

ToLEDo Superia Tube T5

TOLEDO SUPERIA T5 HE 5FT 2800LM 865

0029512

Special purpose lamp	No
Suitable for household illumination	Yes
Safety message	Suitable for totally enclosed fixture



© Feilo Sylvania | Date Printed: 19 Dec 2018