Sylproof Superia LED G3 Emergency

SYLPROOF SUPERIA LED G3 1500mm Twin 4K E3 MW

0048724



Product features

- Sylproof Superia, integrated LED weatherproof luminaire, with UV stabilized flat diffuser and linear prisms designed to achieve uniform lit appearance, optimise light output and to reduce glare, stainless steel diffuser clips and fixing brackets for surface and wall mounting. PC housing, PC diffuser, Non dimmable, 3 hour emergency, 4000K, CRI80, 6600 lm, 50 W, 130 lm/W, nominal average life (h):50000, energy class: A++ A+ A Class I,IK08, IP65.

PRODUCT OVERVIEW

IPC Code	0048724
Product name	SYLPROOF SUPERIA LED G3 1500mm Twin 4K E3 MW
Technology	LED
Housing	PC
Mount	Surface, ceiling mounting, horizontally and vertically wall mounting
Fixture rating	Enclosed
General application	Logistics & Industry
Certifications	EUNEW024
ETIM Class	EC000109
Fixture luminous flux (lm)	6600
Luminaire efficacy (lm/W)	130
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	100
Photobiological Risk Group	RG1
Total power consumption (W)	50
Electrical protection	Class I
Control gear type	Electronic (constant current)
Dimmable	No
Average life (Nominal) (h)	50000
Housing colour	Grey
IP rating	IP65
IK rating	IK08
Product EAN number	5410288487243
Lamps	Yes
Included lamp	INTEGRATED LED

© Feilo Sylvania | Date Printed: 19 Dec 2018

Sylproof Superia LED G3 Emergency

SYLPROOF SUPERIA LED G3 1500mm Twin 4K E3 MW

0048724

DATA TABLE

General data

IPC Code	0048724
Product name	SYLPROOF SUPERIA LED G3 1500mm Twin 4K E3 MW
Technology	LED
Housing	PC
Mount	Surface, ceiling mounting, horizontally and vertically wall mounting
Fixture rating	Enclosed
General application	Logistics & Industry
Operating temperature range (°C)	0°C to +30°C
Certifications	EUNEW024
ETIM Class	EC000109

Optical data

Fixture luminous flux (lm)	6600
Luminaire efficacy (lm/W)	130
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	100
Distribution type	Direct
Photobiological Risk Group	RG1
Emergency duration (h)	3

Electrical data

Total power consumption (W)	50
Mains voltage (V)	220-240V~
Mains frequency (Hz)	50/60Hz
Electrical protection	Class I
Control gear required	No
Control gear type	Electronic (constant current)
Dimmable	No
Drive current (mA)	300
Glow Wire Test (°C)	850
Nominal Frequency (Hz)	50/60Hz

Lifetime data

Lumen maintenance - L70 B50	60000
Lumen maintenance - L80 B10	60000
Lumen maintenance - L90 B50	60000
Average life (Nominal) (h)	50000

Physical data

Housing colour	Grey
IP rating	IP65
IK rating	IK08

© Feilo Sylvania | Date Printed: 19 Dec 2018

Sylproof Superia LED G3 Emergency

SYLPROOF SUPERIA LED G3 1500mm Twin 4K E3 MW

0048724

Diffuser finish	Clear
Diffuser material	PC
Nominal Product Length (mm)	1578
Nominal Product Width (mm)	110
Nominal Product Height (mm)	78
Weight (kg)	2.75


Packaging


Single packaging type	Carton
Product EAN number	5410288487243
Packaging single length / height (cm)	167.2
Packaging single width (cm)	11.6
Packaging single depth (cm)	8.4
DUN14 (outer)	05410288487243
Units per outer package	1
Packaging outer length / height (cm)	167.2
Packaging outer width (cm)	11.6
Packaging outer depth (cm)	8.4


Safety data


Dry applications use only	No

PHOTOMETRY









© Feilo Sylvania | Date Printed: 19 Dec 2018


Sylproof Superia LED G3 Emergency

SYLPROOF SUPERIA LED G3 1500mm Twin 4K E3 MW

0048724

TECHNICAL DRAWINGS






© Feilo Sylvania | Date Printed: 19 Dec 2018

Sylproof Superia LED G3 Emergency

SYLPROOF SUPERIA LED G3 1500mm Twin 4K E3 MW

0048724



© Feilo Sylvania | Date Printed: 19 Dec 2018