

## Sylproof Superia LED G3 Quick connector

*SYLPROOF SUPERIA LED G3 600mm Twin 4K QC DALI*  
0048737



### Product features

- Sylproof Superia, integrated LED weatherproof luminaire with quick connector, UV stabilized flat diffuser and linear prisms designed to achieve uniform lit appearance, optimise light output and to reduce glare, stainless steel diffuser clips and fixing brackets for surface and wall mounting. GRP housing, Polycarbonate diffuser, DALI dimmable, 4000K, CRI80, 2700 lm, 19 W, 140 lm/W, nominal average life (h):50000, energy class: A++ A+ A Class I, IK08, IP65.



## PRODUCT OVERVIEW

IPC Code	0048737
Product name	SYLPROOF SUPERIA LED G3 600mm Twin 4K QC DALI
Technology	LED
Housing	GRP
Mount	Surface, ceiling mounting, horizontally and vertically wall mounting or suspended mounting
Fixture rating	Enclosed
General application	Logistics & Industry
Certifications	EUNEW009
ETIM Class	EC000109
Fixture luminous flux (lm)	2700
Luminaire efficacy (lm/W)	140
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	100
Photobiological Risk Group	RG0
Total power consumption (W)	19
Electrical protection	Class I
Control gear type	Electronic dimmable DALI
Dimmable	Yes
Minimum dimming level (%)	1
Average life (Nominal) (h)	50000
Housing colour	Grey
IP rating	IP65
IK rating	IK08
Product EAN number	5410288487373
Lamps	Yes
Included lamp	INTEGRATED LED

## DATA TABLE

## Sylproof Superia LED G3 Quick connector

*SYLPROOF SUPERIA LED G3 600mm Twin 4K QC DALI*

0048737

### General data

IPC Code	0048737
Product name	SYLPROOF SUPERIA LED G3 600mm Twin 4K QC DALI
Technology	LED
Housing	GRP
Mount	Surface, ceiling mounting, horizontally and vertically wall mounting or suspended mounting
Fixture rating	Enclosed
General application	Logistics & Industry
Operating temperature range (°C)	-20°C to +40°C
Certifications	EUNEW009
ETIM Class	EC000109

### Optical data

Fixture luminous flux (lm)	2700
Luminaire efficacy (lm/W)	140
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	100
Distribution type	Direct
Photobiological Risk Group	RG0

### Electrical data

Total power consumption (W)	19
Mains voltage (V)	220-240V~
Mains frequency (Hz)	0/50/60Hz
Electrical protection	Class I
Control gear required	No
Control gear type	Electronic dimmable DALI
Dimmable	Yes
Minimum dimming level (%)	1
Drive current (mA)	300
Inrush Current (A)	29
Inrush Duration (µs)	180
Glow Wire Test (°C)	850
Nominal Frequency (Hz)	DC/50/60Hz
Max. Luminaires per 10A C Breaker	21
Max. Luminaires per 13A C Breaker	28
Max. Luminaires per 16A C Breaker	36
Max. Luminaires per 20A C Breaker	45
Max. Luminaires per 10A B Breaker	13
Max. Luminaires per 13A B Breaker	17
Max. Luminaires per 16A B Breaker	22
Max. Luminaires per 20A B Breaker	27

### Lifetime data

Lumen maintenance - L70 B50	60000
-----------------------------	-------

## Sylproof Superia LED G3 Quick connector

*SYLPROOF SUPERIA LED G3 600mm Twin 4K QC DALI*  
0048737

Lumen maintenance - L80 B10	60000
Lumen maintenance - L90 B50	60000
Average life (Nominal) (h)	50000

### Physical data

Housing colour	Grey
IP rating	IP65
IK rating	IK08
Diffuser finish	Clear
Diffuser material	Polycarbonate
Nominal Product Length (mm)	665
Nominal Product Width (mm)	110
Nominal Product Height (mm)	78
Weight (kg)	1.18


### Packaging

Single packaging type	Carton
Product EAN number	5410288487373
Packaging single length / height (cm)	77.5
Packaging single width (cm)	11.6
Packaging single depth (cm)	8.4
DUN14 (outer)	05410288487373
Units per outer package	1
Packaging outer length / height (cm)	77.5
Packaging outer width (cm)	11.6
Packaging outer depth (cm)	8.4

### Safety data

Dry applications use only	No
---------------------------	----

## PHOTOMETRY




Distance [m]	Cone diameter [m]	Beam angle [°]	Beam angle [°]	Beam angle [°]
0.5	1.17 1.52	49.8° 65.7°	338° 461° 284°	
1.0	2.35 3.04	49.8° 65.7°	847° 115° 71°	
1.5	3.52 4.57	49.8° 65.7°	376° 81° 32°	
2.0	4.70 6.09	49.8° 65.7°	212° 29° 15°	
2.5	5.87 7.61	49.8° 65.7°	135° 18° 11°	
3.0	7.05 9.13	49.8° 65.7°	94° 13° 8°	

## TECHNICAL DRAWINGS

## Sylproof Superia LED G3 Quick connector SYLPROOF SUPERIA LED G3 600mm Twin 4K QC DALI 0048737



**SYLVANIA** 0048737



This luminaire contains built in LED lamps.

A++

A+

A

B

C

D

E


}


L

E

D

The lamps cannot be changed in the luminaire.

874/2012




This luminaire contains built in LED lamps.

A++

A+

A

B

C

D

E

}


L

E

D

The lamps cannot be changed in the luminaire.

**SYLVANIA** 0048737


874/2012



Sylproof Superia LED G3 Quick connector  
*SYLPROOF SUPERIA LED G3 600mm Twin 4K QC DALI*  
0048737

---