Sylproof Superia LED G3 Quick connector

SYLPROOF SUPERIA LED G3 1500mm S 4K QC SSH01

0048756



Product features

- Sylproof Superia, integrated LED weatherproof luminaire including SylSmart Connected Building (SSH) technology with quick connector, UV stabilized flat diffuser and linear prisms designed to achieve uniform lit appearance, optimise light output and to reduce glare, stainless steel diffuser clips and fixing brackets for surface and wall mounting. L 1578 mm x W 84 mm x H 75 mm size, Polycarbonate housing, Polycarbonate diffuser, Non dimmable, 4000K, CRI80, 4800 lm, 31 W, 155 lm/W, nominal average life (h):50000, energy class: A++ A+ A Class I,IK08, IP65.

PRODUCT OVERVIEW

IPC Code	0048756
Product name	SYLPROOF SUPERIA LED G3 1500mm S 4K QC SSH01
Technology	LED
Housing	Polycarbonate
Mount	Surface, ceiling mounting, horizontally and vertically wall mounting or suspended mounting
Fixture rating	Enclosed
General application	Logistics & Industry
Certifications	EUNEW023
ETIM Class	EC000109
Fixture luminous flux (lm)	4800
Luminaire efficacy (lm/W)	145
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	100
Photobiological Risk Group	RG0
Total power consumption (W)	33
Electrical protection	Class I
Control gear type	Electronic (constant current)
Dimmable	Yes
Average life (Nominal) (h)	50000
Housing colour	Grey
IP rating	IP65
IK rating	IK08
Product EAN number	5410288487564
Lamps	Yes

DATA TABLE

General data

IPC Code	0048756
Product name	SYLPROOF SUPERIA LED G3 1500mm S 4K QC SSH01

© Feilo Sylvania | Date Printed: 20 Dec 2018

Sylproof Superia LED G3 Quick connector

SYLPROOF SUPERIA LED G3 1500mm S 4K QC SSH01

0048756

Technology	LED
Housing	Polycarbonate
Mount	Surface, ceiling mounting, horizontally and vertically wall mounting or suspended mounting
Fixture rating	Enclosed
General application	Logistics & Industry
Operating temperature range (°C)	-20°C to +35°C
Certifications	EUNEW023
ETIM Class	EC000109

Optical data

Fixture luminous flux (lm)	4800
Luminaire efficacy (lm/W)	145
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	100
Distribution type	Direct
Photobiological Risk Group	RG0

Electrical data

Total power consumption (W)	33
Mains voltage (V)	220-240V~
Electrical protection	Class I
Control gear required	No
Control gear type	Electronic (constant current)
Dimmable	Yes
Drive current (mA)	300
Glow Wire Test (°C)	850
Nominal Frequency (Hz)	DC/50/60Hz

Lifetime data

Lumen maintenance - L70 B50	60000
Average life (Nominal) (h)	50000

Physical data

Housing colour	Grey
IP rating	IP65
IK rating	IK08
Diffuser finish	Clear
Diffuser material	Polycarbonate
Nominal Product Length (mm)	1650
Nominal Product Width (mm)	84
Nominal Product Height (mm)	75
Weight (kg)	2.23

Packaging

Single packaging type	Carton

© Feilo Sylvania | Date Printed: 20 Dec 2018

Sylproof Superia LED G3 Quick connector


SYLPROOF SUPERIA LED G3 1500mm S 4K QC SSH01

0048756

Product EAN number	5410288487564
Packaging single length / height (cm)	167.2
Packaging single width (cm)	8.8
Packaging single depth (cm)	8.4
DUN14 (outer)	05410288487564
Units per outer package	1
Packaging outer length / height (cm)	167.2
Packaging outer width (cm)	8.8
Packaging outer depth (cm)	8.4

Safety data

Dry applications use only	No




© Feilo Sylvania | Date Printed: 20 Dec 2018

Sylproof Superia LED G3 Quick connector

SYLPROOF SUPERIA LED G3 1500mm S 4K QC SSH01

0048756



© Feilo Sylvania | Date Printed: 20 Dec 2018