

ToLEDo Vintage A60

TOLEDO™ VINTAGE A60 125LM 820 E27 SL

0027976



Product features

- New and innovative Flexible Filament Chip Technology (FFCT) designed to create the low-lit vintage effect.
- Perfect for hotels, restaurants, heritage lighting, bars and decorative applications.
- The ideal LED solution to replace incandescent vintage GLS A60 lamp.
- Low glare - suitable for low height installation.
- 2000K colour temperature, to create a cosy ambience.
- Golden tinted glass envelope.
- 15,000 hours average rated life. Last 7.5 times longer than incandescent vintage lamps.
- Unique filament construction design - 'Cord' shape.
- Omni-directional light distribution - 300°.
- Low-lumen output to create low-lit effect - 125lm.
- More than 100,000X switching cycles.
- 3 years warranty.
- Environment friendly - no mercury and lower CO2 emissions.



PRODUCT OVERVIEW

IPC Code	0027976
Product name	TOLEDO™ VINTAGE A60 125LM 820 E27 SL
Technology	LED
Watt (Rated) (W)	2.3
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Residential & Consumer,
Certifications	EUTIE103
ETIM Class	EC001959
E-number FI	4740638
Luminous flux (lm)	125
Colour temperature (K)	2000
Light colour	Candlelight
CRI (Ra)	80
Wattage (W)	2.3
Product Voltage (V)	230
Average life (Nominal) (h)	15000
Product EAN number	5410288279763

DATA TABLE

General data

IPC Code	0027976
Product name	TOLEDO™ VINTAGE A60 125LM 820 E27 SL
Technology	LED
Watt (Rated) (W)	2.3
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Residential & Consumer,
Operating temperature rated (°C)	25
Certifications	EUTIE103
ETIM Class	EC001959
E-number FI	4740638

ToLEDo Vintage A60

TOLEDO™ VINTAGE A60 125LM 820 E27 SL

0027976

Optical data

Luminous flux (lm)	125
Luminous flux (Rated) (lm)	125
Colour temperature (K)	2000
Light colour	Candlelight
Colour Code	820
CRI (Ra)	80
Beam angle (Rated) (°)	360

Electrical data

Wattage (W)	2.3
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	1
Product Voltage (V)	230
Lamp power factor	0.5
No. Of switching cycles before premature failures	50000
Lamp Energy Label (class)	A+
kWh per 1000 hours burning time	3
Nominal Frequency (Hz)	50Hz

Lifetime data

Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

Physical data

Nominal Product Length (mm)	104
Nominal Product Diameter (mm)	60
Weight (kg)	0.058

Packaging

Single packaging type	Carton
Product EAN number	5410288279763
Packaging single length / height (cm)	12.0
Packaging single width (cm)	6.6
Packaging single depth (cm)	6.6
DUN14 (inner)	25410288279767
Units per inner package	6
Packaging inner length / height (cm)	20.6
Packaging inner width (cm)	13.9
Packaging inner depth (cm)	13.0
DUN14 (outer)	15410288279760
Units per outer package	60
Packaging outer length / height (cm)	72.5
Packaging outer width (cm)	22.0
Packaging outer depth (cm)	28.5

Safety data

ToLEDo Vintage A60


TOLEDO™ VINTAGE A60 125LM 820 E27 SL

0027976

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

PHOTOMETRY

TECHNICAL DRAWINGS



ToLEDo Vintage A60

TOLEDO™ VINTAGE A60 125LM 820 E27 SL

0027976

