#### **Product features**

Integrated LED spotlight, black RAL 9005, compact and minimalist design, low glare, dark-light detail for increased accentuation and visual comfort, ideal for museum, gallery and high-end retail applications, die-cast aluminium body, passive cooling heatsink, beam angle: 10° intense narrow beam, optics: Fresnel lens for controlled beam, colour temperature: 3000K warm white, total system power: 21W, total fixture output: 503lm, luminaire efficacy: 24lm/W, LOR: 100%, colour rendering: Ra 97 typical, R9 value at 90, LED Chromacity: 3 step MacAdam ellipse, lifetime: >72,000 hours at L80B50, energy class: A++, A+, A, IR/UV free light source without heat radiation, operating voltage: 220-240V / 50-60Hz, drive current: 500mA, electronic driver, dimmable via on-board potentiometer, power factor: 0.9 electrical protection: CLASS II, 1-circuit track adaptor, suitable for Concord Lytespan 1 track, ingress protection rating: IP20, suitable for internal environment only, horizontal rotation: 355°, vertical tilt: 90°, dimensions: Ø80x130x169mm, weight: 0.96kg.

















### PRODUCT OVERVIEW

| IPC Code                    | 2059544                                                  |
|-----------------------------|----------------------------------------------------------|
| Product name                | BEACON ACCENT 97CRI 3K NARROW BEAM L1 ON-BOARD DIM BLACK |
| Technology                  | LED                                                      |
| Housing                     | Die cast Aluminium                                       |
| Mount                       | Single Circuit Track (L1)                                |
| Environment                 | Internal                                                 |
| General application         | Museums & Galleries, Retail                              |
| Certifications              | EUNEW009                                                 |
| ETIM Class                  | EC001744                                                 |
| Fixture luminous flux (Im)  | 503                                                      |
| Luminaire efficacy (lm/W)   | 24                                                       |
| LOR (%)                     | 100                                                      |
| Colour temperature (K)      | 3000                                                     |
| Light colour                | Warm White                                               |
| CRI (Ra)                    | 97                                                       |
| Colour Consistency (SDCM)   | 3                                                        |
| Beam Angle (°)              | 10                                                       |
| Photobiological Risk Group  | Group 1                                                  |
| Total power consumption (W) | 21                                                       |
| Product Voltage (V)         | 240                                                      |
| Electrical protection       | Class II                                                 |
| Control gear type           | Electronic                                               |
| Minimum dimming level (%)   | 95                                                       |
| Average life (Nominal) (h)  | 50000                                                    |
| Housing colour              | Black                                                    |
| IP rating                   | IP20                                                     |
| IK rating                   | IK02                                                     |
| Product EAN number          | 5025768595440                                            |
| Lamps                       | Yes                                                      |
| Included lamp               | INTEGRATED LED                                           |



### **DATA TABLE**

| General data                                                                                                                                                                                                                                                                                                                                                                                          |                                                                      |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------|
| IPC Code                                                                                                                                                                                                                                                                                                                                                                                              | 2059544                                                              |
| Product name                                                                                                                                                                                                                                                                                                                                                                                          | BEACON ACCENT 97CRI 3K NARROW BEAM L1 ON-BOARD DIM BLACK             |
| Technology                                                                                                                                                                                                                                                                                                                                                                                            | LED                                                                  |
| Housing                                                                                                                                                                                                                                                                                                                                                                                               | Die cast Aluminium                                                   |
| Mount                                                                                                                                                                                                                                                                                                                                                                                                 | Single Circuit Track (L1)                                            |
| Environment                                                                                                                                                                                                                                                                                                                                                                                           | Internal                                                             |
| General application                                                                                                                                                                                                                                                                                                                                                                                   | Museums & Galleries, Retail                                          |
| Certifications                                                                                                                                                                                                                                                                                                                                                                                        | EUNEW009                                                             |
| ETIM Class                                                                                                                                                                                                                                                                                                                                                                                            | EC001744                                                             |
| Optical data                                                                                                                                                                                                                                                                                                                                                                                          |                                                                      |
| Fixture luminous flux (Im)                                                                                                                                                                                                                                                                                                                                                                            | 503                                                                  |
| Luminaire efficacy (Im/W)                                                                                                                                                                                                                                                                                                                                                                             | 24                                                                   |
| LOR (%)                                                                                                                                                                                                                                                                                                                                                                                               | 100                                                                  |
| Colour temperature (K)                                                                                                                                                                                                                                                                                                                                                                                | 3000                                                                 |
| Light colour                                                                                                                                                                                                                                                                                                                                                                                          | Warm White                                                           |
| CRI (Ra)                                                                                                                                                                                                                                                                                                                                                                                              | 97                                                                   |
| Colour Consistency (SDCM)                                                                                                                                                                                                                                                                                                                                                                             | 3                                                                    |
| Adjustable chromaticity                                                                                                                                                                                                                                                                                                                                                                               | N                                                                    |
| Beam Angle (°)                                                                                                                                                                                                                                                                                                                                                                                        | 10                                                                   |
| Distribution type                                                                                                                                                                                                                                                                                                                                                                                     | Direct                                                               |
| Photobiological Risk Group                                                                                                                                                                                                                                                                                                                                                                            | Group 1                                                              |
| i notobiological Mak Group                                                                                                                                                                                                                                                                                                                                                                            | Gloup I                                                              |
|                                                                                                                                                                                                                                                                                                                                                                                                       | Cloup I                                                              |
| Electrical data  Total power consumption (W)                                                                                                                                                                                                                                                                                                                                                          | 21                                                                   |
| Electrical data                                                                                                                                                                                                                                                                                                                                                                                       |                                                                      |
| Electrical data  Total power consumption (W)                                                                                                                                                                                                                                                                                                                                                          | 21                                                                   |
| Electrical data  Total power consumption (W)  Mains voltage (V)                                                                                                                                                                                                                                                                                                                                       | 21<br>220-240V~                                                      |
| Electrical data  Total power consumption (W)  Mains voltage (V)  Product Voltage (V)                                                                                                                                                                                                                                                                                                                  | 21<br>220-240V~<br>240                                               |
| Electrical data  Total power consumption (W)  Mains voltage (V)  Product Voltage (V)  Lamp power factor                                                                                                                                                                                                                                                                                               | 21<br>220-240V~<br>240<br>0.9                                        |
| Electrical data  Total power consumption (W)  Mains voltage (V)  Product Voltage (V)  Lamp power factor  Electrical protection                                                                                                                                                                                                                                                                        | 21<br>220-240V~<br>240<br>0.9<br>Class II                            |
| Electrical data  Total power consumption (W)  Mains voltage (V)  Product Voltage (V)  Lamp power factor  Electrical protection  Control gear type                                                                                                                                                                                                                                                     | 21<br>220-240V~<br>240<br>0.9<br>Class II<br>Electronic              |
| Electrical data  Total power consumption (W)  Mains voltage (V)  Product Voltage (V)  Lamp power factor  Electrical protection  Control gear type  Transformer required                                                                                                                                                                                                                               | 21 220-240V~ 240 0.9 Class II Electronic Yes                         |
| Electrical data  Total power consumption (W)  Mains voltage (V)  Product Voltage (V)  Lamp power factor  Electrical protection  Control gear type  Transformer required  Minimum dimming level (%)                                                                                                                                                                                                    | 21 220-240V~ 240 0.9 Class II Electronic Yes 95                      |
| Electrical data  Total power consumption (W)  Mains voltage (V)  Product Voltage (V)  Lamp power factor  Electrical protection  Control gear type  Transformer required  Minimum dimming level (%)  Inrush Current (A)                                                                                                                                                                                | 21 220-240V~ 240 0.9 Class II Electronic Yes 95 15                   |
| Electrical data  Total power consumption (W)  Mains voltage (V)  Product Voltage (V)  Lamp power factor  Electrical protection  Control gear type  Transformer required  Minimum dimming level (%)  Inrush Current (A)  Inrush Duration (µs)                                                                                                                                                          | 21 220-240V~ 240 0.9 Class II Electronic Yes 95 15 20                |
| Electrical data  Total power consumption (W)  Mains voltage (V)  Product Voltage (V)  Lamp power factor  Electrical protection  Control gear type  Transformer required  Minimum dimming level (%)  Inrush Current (A)  Inrush Duration (µs)  Glow Wire Test (°C)                                                                                                                                     | 21 220-240V~ 240 0.9 Class II Electronic Yes 95 15 20 650            |
| Electrical data  Total power consumption (W)  Mains voltage (V)  Product Voltage (V)  Lamp power factor  Electrical protection  Control gear type  Transformer required  Minimum dimming level (%)  Inrush Current (A)  Inrush Duration (µs)  Glow Wire Test (°C)  Nominal Frequency (Hz)                                                                                                             | 21 220-240V~ 240 0.9 Class II Electronic Yes 95 15 20 650 50/60Hz    |
| Electrical data  Total power consumption (W)  Mains voltage (V)  Product Voltage (V)  Lamp power factor  Electrical protection  Control gear type  Transformer required  Minimum dimming level (%)  Inrush Current (A)  Inrush Duration (µs)  Glow Wire Test (°C)  Nominal Frequency (Hz)  Max. Luminaires per 16A C Breaker                                                                          | 21 220-240V~ 240 0.9 Class II Electronic Yes 95 15 20 650 50/60Hz    |
| Electrical data  Total power consumption (W)  Mains voltage (V)  Product Voltage (V)  Lamp power factor  Electrical protection  Control gear type  Transformer required  Minimum dimming level (%)  Inrush Current (A)  Inrush Duration (µs)  Glow Wire Test (°C)  Nominal Frequency (Hz)  Max. Luminaires per 16A C Breaker                                                                          | 21 220-240V~ 240 0.9 Class II Electronic Yes 95 15 20 650 50/60Hz 80 |
| Electrical data  Total power consumption (W)  Mains voltage (V)  Product Voltage (V)  Lamp power factor  Electrical protection  Control gear type  Transformer required  Minimum dimming level (%)  Inrush Current (A)  Inrush Duration (µs)  Glow Wire Test (°C)  Nominal Frequency (Hz)  Max. Luminaires per 16A C Breaker  Lifetime data  Lumen maintenance - L70 B50                              | 21 220-240V~ 240 0.9 Class II Electronic Yes 95 15 20 650 50/60Hz 80 |
| Electrical data  Total power consumption (W)  Mains voltage (V)  Product Voltage (V)  Lamp power factor  Electrical protection  Control gear type  Transformer required  Minimum dimming level (%)  Inrush Current (A)  Inrush Duration (µs)  Glow Wire Test (°C)  Nominal Frequency (Hz)  Max. Luminaires per 16A C Breaker  Lifetime data  Lumen maintenance - L70 B50  Lumen maintenance - L70 B10 | 21 220-240V~ 240 0.9 Class II Electronic Yes 95 15 20 650 50/60Hz 80 |

| Lumen maintenance - L90 B20 | 36000 |  |
|-----------------------------|-------|--|
| Lumen maintenance - L90 B10 | 33000 |  |
| Average life (Nominal) (h)  | 50000 |  |


#### Physical data


| i ilyolodi data               |                     |
|-------------------------------|---------------------|
| Vertical Tilt (°)             | 90                  |
| Horizontal rotation (°)       | 355                 |
| Housing colour                | Black               |
| IP rating                     | IP20                |
| IK rating                     | IK02                |
| Reflector finish              | Aluminium Reflector |
| Nominal Product Width (mm)    | 130                 |
| Nominal Product Height (mm)   | 169                 |
| Nominal Product Diameter (mm) | 80                  |
| Weight (kg)                   | 0.7                 |

### Packaging

| 6 6                                   |                |
|---------------------------------------|----------------|
| Single packaging type                 | Carton         |
| Product EAN number                    | 5025768595440  |
| Packaging single length / height (cm) | 16.0           |
| Packaging single width (cm)           | 17.6           |
| Packaging single depth (cm)           | 18.2           |
| DUN14 (outer)                         | 05025768595440 |
| Units per outer package               | 1              |
| Packaging outer length / height (cm)  | 16.0           |
| Packaging outer width (cm)            | 17.6           |
| Packaging outer depth (cm)            | 18.2           |

### **PHOTOMETRY**





### **TECHNICAL DRAWINGS**





