Start Waterproof LED G3 fixed output

START WATERPROOF LED G3 1200MM S 4K

0048613



Product features

- Start Waterproof, integrated LED weatherproof luminaire, with UV stabilized flat diffuser and linear prisms designed to achieve uniform lit appearance, optimise light output and to reduce glare, stainless steel diffuser clips and fixing brackets for surface mounting. Polycarbonate housing, Polycarbonate diffuser, 2900lm, 22W, 132lm/W, 4000K, drive current 350mA, Non dimmable, CRI80, IP65, IK08, Class I, nominal average life (h):50000, 1278mm x 84mm x 75mm ,energy class: A++ A+ A

PRODUCT OVERVIEW

IPC Code	0048613
Product name	START WATERPROOF LED G3 1200MM S 4K
Technology	LED
Housing	Polycarbonate
Mount	Ceiling Mounting and Suspended Mounting
Fixture rating	Enclosed
General application	Logistics & Industry
Certifications	EUNEW009
ETIM Class	EC002892
E-number FI	4306947
E-number SE	7214439
Fixture luminous flux (lm)	2900
Luminaire efficacy (lm/W)	132
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	100
Glare control	25
Photobiological Risk Group	RG0
Total power consumption (W)	22
Electrical protection	Class I
Control gear type	Electronic (constant current)
Dimmable	No
LED Flickering Rate	High (>40%)
Average life (Nominal) (h)	50000
Housing colour	Grey
IP rating	IP65
IK rating	IK08
Product EAN number	5410288486130
Lamps	Yes
Included lamp	INTEGRATED LED

© Feilo Sylvania | Date Printed: 21 Dec 2018

Start Waterproof LED G3 fixed output

START WATERPROOF LED G3 1200MM S 4K

0048613

DATA TABLE

General data

IPC Code	0048613
Product name	START WATERPROOF LED G3 1200MM S 4K
Technology	LED
Housing	Polycarbonate
Mount	Ceiling Mounting and Suspended Mounting
Fixture rating	Enclosed
General application	Logistics & Industry
Operating temperature range (°C)	-20°C to +40°C
Certifications	EUNEW009
ETIM Class	EC002892
E-number FI	4306947
E-number SE	7214439

Optical data

Fixture luminous flux (lm)	2900
Luminaire efficacy (lm/W)	132
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	100
Distribution type	Direct
Glare control	25
Photobiological Risk Group	RG0

Electrical data

Total power consumption (W)	22
Mains voltage (V)	220-240V~
THD (at 230 V, 50 Hz, full load, at 100% dimming level) xx.x %	20.0
Mains frequency (Hz)	50/60Hz
Electrical protection	Class I
Control gear required	No
Control gear type	Electronic (constant current)
Dimmable	No
Drive current (mA)	350
Inrush Current (A)	4
Inrush Duration (µs)	32
Glow Wire Test (°C)	850
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	High (>40%)
Max. Luminaires per 10A C Breaker	70
Max. Luminaires per 13A C Breaker	90
Max. Luminaires per 16A C Breaker	110
Max. Luminaires per 20A C Breaker	140
Max. Luminaires per 10A B Breaker	60

© Feilo Sylvania | Date Printed: 21 Dec 2018

Start Waterproof LED G3 fixed output

START WATERPROOF LED G3 1200MM S 4K

0048613

Max. Luminaires per 13A B Breaker	80
Max. Luminaires per 16A B Breaker	100
Max. Luminaires per 20A B Breaker	125

Lifetime data

Lumen maintenance - L70 B50	60000
Lumen maintenance - L70 B20	60000
Lumen maintenance - L70 B10	60000
Lumen maintenance - L80 B50	60000
Lumen maintenance - L80 B20	60000
Lumen maintenance - L80 B10	60000
Lumen maintenance - L90 B50	59000
Lumen maintenance - L90 B20	53000
Lumen maintenance - L90 B10	50000
Average life (Nominal) (h)	50000

Physical data

Housing colour	Grey
IP rating	IP65
IK rating	IK08
Diffuser finish	Clear
Diffuser material	Polycarbonate
Nominal Product Length (mm)	1278
Nominal Product Width (mm)	84
Nominal Product Height (mm)	75
Weight (kg)	1.61

Packaging

Single packaging type	Carton
Product EAN number	5410288486130
Packaging single length / height (cm)	137.2
Packaging single width (cm)	8.8
Packaging single depth (cm)	8.4
DUN14 (outer)	05410288486130
Units per outer package	1
Packaging outer length / height (cm)	137.2
Packaging outer width (cm)	8.8
Packaging outer depth (cm)	8.4

Safety data

Dry applications use only	No


PHOTOMETRY


© Feilo Sylvania | Date Printed: 21 Dec 2018

Start Waterproof LED G3 fixed output

START WATERPROOF LED G3 1200MM S 4K


0048613





TECHNICAL DRAWINGS






© Feilo Sylvania | Date Printed: 21 Dec 2018

Start Waterproof LED G3 fixed output

START WATERPROOF LED G3 1200MM S 4K

0048613



© Feilo Sylvania | Date Printed: 21 Dec 2018