

Start Waterproof LED G3 fixed output

START WATERPROOF LED G3 1500MM S 4K

0048623



Product features

- Start Waterproof, integrated LED weatherproof luminaire, with UV stabilized flat diffuser and linear prisms designed to achieve uniform lit appearance, optimise light output and to reduce glare, stainless steel diffuser clips and fixing brackets for surface mounting. Polycarbonate housing, Polycarbonate diffuser, 4100lm, 33W, 125lm/W, 4000K, drive current 1050mA, Non dimmable, CRI80, IP65, IK08, Class I, nominal average life (h):50000, 1578mm x 84mm x 75mm ,energy class: A++ A+ A



PRODUCT OVERVIEW

IPC Code	0048623
Product name	START WATERPROOF LED G3 1500MM S 4K
Technology	LED
Housing	Polycarbonate
Mount	Ceiling Mounting and Suspended Mounting
Fixture rating	Enclosed
General application	Logistics & Industry
Certifications	EUNEW009
ETIM Class	EC002892
E-number FI	4306953
E-number SE	7214441
Fixture luminous flux (lm)	4100
Luminaire efficacy (lm/W)	125
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	100
Glare control	25
Photobiological Risk Group	RG0
Total power consumption (W)	33
Electrical protection	Class I
Control gear type	Electronic (constant current)
Dimmable	No
LED Flickering Rate	High (>40%)
Average life (Nominal) (h)	50000
Housing colour	Grey
IP rating	IP65
IK rating	IK08
Product EAN number	5410288486239
Lamps	Yes
Included lamp	INTEGRATED LED

Start Waterproof LED G3 fixed output

START WATERPROOF LED G3 1500MM S 4K
0048623

DATA TABLE

General data

IPC Code	0048623
Product name	START WATERPROOF LED G3 1500MM S 4K
Technology	LED
Housing	Polycarbonate
Mount	Ceiling Mounting and Suspended Mounting
Fixture rating	Enclosed
General application	Logistics & Industry
Operating temperature range (°C)	-20°C to +40°C
Certifications	EUNEW009
ETIM Class	EC002892
E-number FI	4306953
E-number SE	7214441

Optical data

Fixture luminous flux (lm)	4100
Luminaire efficacy (lm/W)	125
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	100
Distribution type	Direct
Glare control	25
Photobiological Risk Group	RG0

Electrical data

Total power consumption (W)	33
Mains voltage (V)	220-240V~
Lamp power factor	0.93
THD (at 230 V, 50 Hz, full load, at 100% dimming level) xx.x %	16.0
Mains frequency (Hz)	50/60Hz
Electrical protection	Class I
Control gear required	No
Control gear type	Electronic (constant current)
Dimmable	No
Drive current (mA)	1050
Inrush Current (A)	5
Inrush Duration (µs)	37
Glow Wire Test (°C)	850
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	High (>40%)
Max. Luminaires per 10A C Breaker	40
Max. Luminaires per 13A C Breaker	50
Max. Luminaires per 16A C Breaker	60
Max. Luminaires per 20A C Breaker	80

Start Waterproof LED G3 fixed output START WATERPROOF LED G3 1500MM S 4K 0048623

Max. Luminaires per 10A B Breaker	35
Max. Luminaires per 13A B Breaker	45
Max. Luminaires per 16A B Breaker	55
Max. Luminaires per 20A B Breaker	70

Lifetime data

Lumen maintenance - L70 B50	60000
Lumen maintenance - L70 B20	60000
Lumen maintenance - L70 B10	60000
Lumen maintenance - L80 B50	60000
Lumen maintenance - L80 B20	60000
Lumen maintenance - L80 B10	60000
Lumen maintenance - L90 B50	59000
Lumen maintenance - L90 B20	53000
Lumen maintenance - L90 B10	50000
Average life (Nominal) (h)	50000

Physical data

Housing colour	Grey
IP rating	IP65
IK rating	IK08
Diffuser finish	Clear
Diffuser material	Polycarbonate
Nominal Product Length (mm)	1578
Nominal Product Width (mm)	84
Nominal Product Height (mm)	75
Weight (kg)	2.08

Packaging

Single packaging type	Carton
Product EAN number	5410288486239
Packaging single length / height (cm)	167.2
Packaging single width (cm)	8.8
Packaging single depth (cm)	8.4
DUN14 (outer)	05410288486239
Units per outer package	1
Packaging outer length / height (cm)	167.2
Packaging outer width (cm)	8.8
Packaging outer depth (cm)	8.4

Safety data

Dry applications use only	No
---------------------------	----


PHOTOMETRY

Start Waterproof LED G3 fixed output START WATERPROOF LED G3 1500MM S 4K 0048623

0.5	1.39 1.37	E(0°) E(C90) E(C0)	8789 874 894
1.0	2.78 2.75	E(0°) E(C90) E(C0)	1442 148 149
1.5	4.17 4.10	E(0°) E(C90) E(C0)	541 64 66
2.0	5.57 5.47	E(0°) E(C90) E(C0)	361 38 37
2.5	6.96 6.83	E(0°) E(C90) E(C0)	231 23 24
3.0	8.35 8.20	E(0°) E(C90) E(C0)	160 14 17

Distance [m] Cone diameter [m] Illuminance [lx]

— C0 - C180 (Half beam angle: 107.6°)
— C90 - C270 (Half beam angle: 106.6°)



TECHNICAL DRAWINGS



SYLVANIA 0048623

This luminaire contains built in LED lamps.


}

L
E
D

The lamps cannot be changed in the luminaire.

874/2012

Start Waterproof LED G3 fixed output *START WATERPROOF LED G3 1500MM S 4K* 0048623



This luminaire contains built in LED lamps.

The lamps cannot be changed in the luminaire.

SYLVANIA 0048623

874/2012

A++
A+
A
~~B~~
~~C~~
~~D~~
~~E~~

LED

EUROPEAN UNION

Detailed description: The image shows a rectangular energy label with a blue border. On the left, there is a blue icon of a lamp. To its right, the text reads 'This luminaire contains built in LED lamps.' Below this, a white box contains the text 'The lamps cannot be changed in the luminaire.' In the center, there is a vertical energy efficiency scale with seven colored arrows pointing right, labeled A++, A+, A, B, C, D, and E from top to bottom. A large red 'X' is drawn over the B, C, D, and E categories. To the right of the scale, a blue bracket groups the A++, A+, and A categories, with the letters 'L', 'E', and 'D' stacked vertically next to it. In the top right corner of the label is the European Union flag. At the bottom left, the 'SYLVANIA' logo is in green, followed by the product code '0048623'. At the bottom right, the reference number '874/2012' is printed.