

ToLEDo GLS DIMMABLE

ToLEDo GLS V4 DIM FR 1150lm 865 E27 SL

0026627



Product features

- Compact and elegant design *f*•1150lm - suitable for replacing 80W incandescent GLS lamp. *ff*•86% energy saving compared to incandescent lamp. *•ff*Instant light at the flick of a switch *ff*•Uniform light distribution *ff*•Colour temperatures - 6500K *ff*•Good colour rendering (CRI 80) *ff*•Perfect for hotels, restaurants, lobbies, corridors, stairwells, reception areas *ff*•Lower maintenance costs •A+ energy rating - 105 lm/W •Dimmable on approved dimmers



PRODUCT OVERVIEW

IPC Code	0026627
Product name	ToLEDo GLS V4 DIM FR 1150lm 865 E27 SL
Technology	LED
Watt (Rated) (W)	11
Lamp shape	GLS
Cap/Base	E27
Lamp finish	Frosted
General application	Hospitality, Residential & Consumer
Certifications	EUTIE103
ETIM Class	EC001959
E-number FI	4740504
Fixture luminous flux (lm)	RPLA01 : Royalty LED Lamp Single Colour
Luminous flux (lm)	1150
Colour temperature (K)	6500
Light colour	Daylight
CRI (Ra)	80
Colour Consistency (SDCM)	6
Wattage (W)	11
Dimmable	Yes
Average life (Nominal) (h)	15000
Product EAN number	5410288266275

DATA TABLE

General data

IPC Code	0026627
Product name	ToLEDo GLS V4 DIM FR 1150lm 865 E27 SL
Technology	LED
Watt (Rated) (W)	11
Lamp shape	GLS
Cap/Base	E27
Lamp finish	Frosted
General application	Hospitality, Residential & Consumer
Operating temperature range (°C)	109

ToLEDo GLS DIMMABLE

ToLEDo GLS V4 DIM FR 1150lm 865 E27 SL
0026627

Certifications	EUTIE103
ETIM Class	EC001959
E-number FI	4740504

Optical data

Fixture luminous flux (lm)	RPLA01 : Royalty LED Lamp Single Colour
Luminous flux (lm)	1150
Luminous flux (Rated) (lm)	1150
Colour temperature (K)	6500
Light colour	Daylight
CRI (Ra)	80
Colour Consistency (SDCM)	6
Adjustable chromaticity	N
Lumen maintenance at end of nominal life (%)	70

Electrical data

Wattage (W)	11
Equivalent watt (W)	80
Starting time (max) (s)	0.05
Warm-up time to 60% of full light (max) (s)	< 1s => 60%
Mains voltage (V)	220-240V~
Lamp power factor	0.5
Control gear required	No
No. Of switching cycles before premature failures	50000
Transformer required	No
Dimmable	Yes
Drive current (mA)	52
Lamp Energy Label (class)	A+
Energy efficiency level	A+
kWh per 1000 hours burning time	11

Lifetime data

Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

Physical data

Nominal Product Diameter (mm)	109
Max. Lamp Diameter (mm) - D	60
Weight (kg)	0.069

Packaging

Single packaging type	Carton
Product EAN number	5410288266275
Packaging single length / height (cm)	11.3
Packaging single width (cm)	6.4
Packaging single depth (cm)	6.4
DUN14 (inner)	25410288266279

ToLEDo GLS DIMMABLE

ToLEDo GLS V4 DIM FR 1150lm 865 E27 SL


0026627

Units per inner package	6
Packaging inner length / height (cm)	20.4
Packaging inner width (cm)	13.4
Packaging inner depth (cm)	13.7
DUN14 (outer)	15410288266272
Units per outer package	60
Packaging outer length / height (cm)	72.4
Packaging outer width (cm)	22.2
Packaging outer depth (cm)	29.7

Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Intended purpose	No
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

TECHNICAL DRAWINGS



ToLEDo GLS DIMMABLE
ToLEDo GLS V4 DIM FR 1150lm 865 E27 SL
0026627

