

ToLEDo GLS DIMMABLE

ToLEDo GLS V4 DIM FR 1060lm 827 E27 SL

0026683



Product features

- Compact and elegant design *f*•1060lm - suitable for replacing 75W incandescent GLS lamp. *ff*•85% energy saving compared to incandescent lamp. •*ff*Instant light at the flick of a switch *ff*•Uniform light distribution *ff*•Colour temperatures - 2700K *ff*•Good colour rendering (CRI 80) *ff*•Perfect for hotels, restaurants, lobbies, corridors, stairwells, reception areas *ff*•Lower maintenance costs •A+ energy rating - 96 lm/W •Dimmable on approved dimmers



PRODUCT OVERVIEW

IPC Code	0026683
Product name	ToLEDo GLS V4 DIM FR 1060lm 827 E27 SL
Technology	LED
Watt (Rated) (W)	11
Lamp shape	GLS
Cap/Base	E27
Lamp finish	Frosted
General application	Hospitality, Residential & Consumer
Certifications	EUTIE103
ETIM Class	EC001959
E-number FI	4740295
Fixture luminous flux (lm)	RPLA01 : Royalty LED Lamp Single Colour
Luminous flux (lm)	1060
Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Colour Consistency (SDCM)	6
Wattage (W)	11
Average life (Nominal) (h)	25000
Product EAN number	5410288266831

DATA TABLE

General data

IPC Code	0026683
Product name	ToLEDo GLS V4 DIM FR 1060lm 827 E27 SL
Technology	LED
Watt (Rated) (W)	11
Lamp shape	GLS
Cap/Base	E27
Lamp finish	Frosted
General application	Hospitality, Residential & Consumer
Operating temperature range (°C)	109
Certifications	EUTIE103

ToLEDo GLS DIMMABLE

ToLEDo GLS V4 DIM FR 1060lm 827 E27 SL

0026683

ETIM Class	EC001959
E-number FI	4740295

Optical data

Fixture luminous flux (lm)	RPLA01 : Royalty LED Lamp Single Colour
Luminous flux (lm)	1060
Luminous flux (Rated) (lm)	1060
Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Colour Consistency (SDCM)	6
Adjustable chromaticity	N
Lumen maintenance at end of nominal life (%)	70

Electrical data

Wattage (W)	11
Equivalent watt (W)	75
Starting time (max) (s)	0.05
Warm-up time to 60% of full light (max) (s)	< 1s => 60%
Current (A)	0.069
Mains voltage (V)	220-240V~
Lamp power factor	0.85
Control gear required	No
No. Of switching cycles before premature failures	50000
Transformer required	No
Drive current (mA)	52
Lamp Energy Label (class)	A+
Energy efficiency level	A+
kWh per 1000 hours burning time	13

Lifetime data

Average life (Nominal) (h)	25000
Average life (Rated) (h)	25000

Physical data

Nominal Product Diameter (mm)	109
Max. Lamp Diameter (mm) - D	60
Weight (kg)	0.111

Packaging

Single packaging type	Carton
Product EAN number	5410288266831
Packaging single length / height (cm)	14.0
Packaging single width (cm)	7.0
Packaging single depth (cm)	7.0
DUN14 (inner)	25410288266835
Units per inner package	6

ToLEDo GLS DIMMABLE

ToLEDo GLS V4 DIM FR 1060lm 827 E27 SL


0026683

Packaging inner length / height (cm)	23.4
Packaging inner width (cm)	16.1
Packaging inner depth (cm)	17.7
DUN14 (outer)	15410288266838
Units per outer package	60
Packaging outer length / height (cm)	82.7
Packaging outer width (cm)	25.3
Packaging outer depth (cm)	38.3

Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Intended purpose	No
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

TECHNICAL DRAWINGS



ToLEDo GLS DIMMABLE

ToLEDo GLS V4 DIM FR 1060lm 827 E27 SL

0026683

