

Rubico SylSmart LED


RUBICO LED 600x600 HE 4K SSH01 EM3

0044279



Product features

- RUBICO LED 600x600 HE 4K SSH01 EM3 is a direct / indirect low glare luminaire for office and education applications. Ceiling recessed 600x600mm. Micro Prismatic optics. White RAL 9016. SylSmart SSH controlled. 3 hours emergency operation with integral batteries. 4000K Neutral White LED, Typical CRI=85, chromaticity tolerance of 3-step MacAdam ellipse, lumen package of 3,500lm, total power consumption 36W, efficacy of 97lm/W . Lumen maintenance of L80B10 at 60,000 hours, UGR<19. IK07, IP20, Electrical Protection Class I. PC diffuser, Glow Wire test 850°C



PRODUCT OVERVIEW

IPC Code	0044279
Product name	RUBICO LED 600x600 HE 4K SSH01 EM3
Technology	LED
Mount	Recessed
General application	Education, Hospitality, Office, Retail
Certifications	EUNEW022
ETIM Class	EC002892
Fixture luminous flux (lm)	3500
Luminous flux (lm)	3500
Luminaire efficacy (lm/W)	97
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Glare control	UGR<19
Photobiological Risk Group	0
Luminous flux (emergency) (lm)	367
Total power consumption (W)	36
Electrical protection	Class I
Housing colour	White RAL 9016
IP rating	IP20
IK rating	IK07
Product EAN number	5410288442792
Lamps	Yes
Included lamp	INTEGRATED LED

DATA TABLE

General data

IPC Code	0044279
Product name	RUBICO LED 600x600 HE 4K SSH01 EM3
Technology	LED

Rubico SylSmart LED

RUBICO LED 600x600 HE 4K SSH01 EM3

0044279

Mount	Recessed
General application	Education,Hospitality,Office,Retail
Operating temperature range (°C)	+5°C to +50°C
Certifications	EUNEW022
ETIM Class	EC002892

Optical data

Fixture luminous flux (lm)	3500
Luminous flux (lm)	3500
Luminaire efficacy (lm/W)	97
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Distribution type	Direct / Indirect
Glare control	UGR<19
Photobiological Risk Group	0
Luminous flux (emergency) (lm)	367
Emergency duration (h)	3.0

Electrical data

Total power consumption (W)	36
Mains voltage (V)	220-240V~
Electrical protection	Class I
Drive current (mA)	600
Glow Wire Test (°C)	850
Lamp Energy Label (class)	A+
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	21
Max. Luminaires per 13A C Breaker	28
Max. Luminaires per 16A C Breaker	35
Max. Luminaires per 20A C Breaker	45
Max. Luminaires per 10A B Breaker	13
Max. Luminaires per 13A B Breaker	17
Max. Luminaires per 16A B Breaker	21
Max. Luminaires per 20A B Breaker	27

Lifetime data

Lumen maintenance - L70 B50	60000
Lumen maintenance - L70 B20	60000
Lumen maintenance - L70 B10	60000
Lumen maintenance - L80 B50	60000
Lumen maintenance - L80 B20	60000
Lumen maintenance - L80 B10	60000
Lumen maintenance - L90 B50	35000
Lumen maintenance - L90 B20	31000
Lumen maintenance - L90 B10	28500

Physical data

Housing colour	White RAL 9016
----------------	----------------

Rubico SylSmart LED





RUBICO LED 600x600 HE 4K SSH01 EM3
0044279

IP rating	IP20
IK rating	IK07
Diffuser finish	Micro Prismatic optic (MPO) with Satin Side diffuser
Diffuser material	Polycarbonate
Nominal Product Length (mm)	596
Nominal Product Width (mm)	596
Nominal Product Height (mm)	80
Weight (kg)	5.2

Packaging

Single packaging type	Carton
Product EAN number	5410288442792
Packaging single length / height (cm)	65.0
Packaging single width (cm)	65.0
Packaging single depth (cm)	11.0
DUN14 (outer)	05410288442792
Units per outer package	1
Packaging outer length / height (cm)	65.0
Packaging outer width (cm)	62.0
Packaging outer depth (cm)	11.0

PHOTOMETRY




Rubico SylSmart LED

RUBICO LED 600x600 HE 4K SSH01 EM3

0044279

TECHNICAL DRAWINGS



SYLVANIA 0044279

 This luminaire contains built in LED lamps.

 } LED

The lamps cannot be changed in the luminaire.

874/2012 

Rubico SylSmart LED


RUBICO LED 600x600 HE 4K SSH01 EM3

0044279



This luminaire contains built in LED lamps.

The lamps cannot be changed in the luminaire.



SYLVANIA 0044279 874/2012