

Start Bulkhead LED IP65 Round

START BULKHEAD LED IP65 ROUND 4K 1500LM

0049176



Product features

- LED exterior bulkhead, round, comes with 2m cable, white polycarbonate body, 1501LM, 18W, 83lm/W, 4000K, Driver Current 135mA, CRI80, , non-dimmable, IP65, IK08, 25000hrs (L70), (LxWxD) 324x324x80mm



PRODUCT OVERVIEW

IPC Code	0049176
Product name	START BULKHEAD LED IP65 ROUND 4K 1500LM
Technology	LED
Housing	PC
Mount	Surface Mounted
General application	Logistics & Industry, Residential & Consumer
Certifications	EUNEW009
ETIM Class	EC002892
E-number SE	7505119
Fixture luminous flux (lm)	1501
Luminous flux (lm)	1501
Luminaire efficacy (lm/W)	83.4
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Photobiological Risk Group	Group 1
Total power consumption (W)	18
Electrical protection	Class II
Dimmable	No
Housing colour	White
IP rating	IP65
IK rating	IK08
Product EAN number	5410288491769
Lamps	No
Included lamp	INTEGRATED LED

DATA TABLE

General data

IPC Code	0049176
Product name	START BULKHEAD LED IP65 ROUND 4K 1500LM

Start Bulkhead LED IP65 Round

START BULKHEAD LED IP65 ROUND 4K 1500LM

0049176

Technology	LED
Housing	PC
Mount	Surface Mounted
General application	Logistics & Industry, Residential & Consumer
Certifications	EUNEW009
ETIM Class	EC002892
E-number SE	7505119

Optical data

Fixture luminous flux (lm)	1501
Luminous flux (lm)	1501
Luminaire efficacy (lm/W)	83.4
LOR (%)	100
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Photobiological Risk Group	Group 1

Electrical data

Total power consumption (W)	18
Current (A)	0.09
Mains voltage (V)	220-240V~
Electrical protection	Class II
Dimmable	No
Inrush Duration (µs)	600
Glow Wire Test (°C)	850
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	18
Max. Luminaires per 16A C Breaker	30

Lifetime data

Lumen maintenance - L70 B50	25000
Lumen maintenance - L70 B20	23000
Lumen maintenance - L70 B10	21000
Lumen maintenance - L80 B50	19000
Lumen maintenance - L80 B20	17500
Lumen maintenance - L80 B10	16000

Physical data

Housing colour	White
IP rating	IP65
IK rating	IK08
Diffuser finish	Opal
Diffuser material	PC
Nominal Product Length (mm)	80.5
Nominal Product Width (mm)	324
Nominal Product Height (mm)	324
Weight (kg)	1.035

Start Bulkhead LED IP65 Round

START BULKHEAD LED IP65 ROUND 4K 1500LM
0049176


Packaging

Single packaging type	Carton
Product EAN number	5410288491769
Packaging single length / height (cm)	33.5
Packaging single width (cm)	11.5
Packaging single depth (cm)	33.5
DUN14 (outer)	15410288491766
Units per outer package	6
Packaging outer length / height (cm)	69.0
Packaging outer width (cm)	36.5
Packaging outer depth (cm)	35.5

Safety data

Optimal operating condition (°C)	-10-40
----------------------------------	--------

PHOTOMETRY



Start Bulkhead LED IP65 Round START BULKHEAD LED IP65 ROUND 4K 1500LM 0049176

SYLVANIA 0049176

 This luminaire contains built in LED lamps.

A++
A+
A
B
C
D
E

LED

The lamps cannot be changed in the luminaire.

874/2012 

 This luminaire contains built in LED lamps.

A++
A+
A
B
C
D
E

LED

The lamps cannot be changed in the luminaire.

SYLVANIA 0049176  874/2012