

Refled Sylgro SYLGRO 0020963



Product features

 SylGro LED lamps for home plants growing applications have a E27 base, 17W/120-240V, IP44 rated, two main specific spectrum with Red and Blue light, very high photosynthesis efficacy up to 2.3 mol/J and a lifetime of 25,000hrs L70B50.











PRODUCT OVERVIEW

IPC Code	0020963
Product name	SYLGRO
Technology	LED
Watt (Rated) (W)	17
Туре	R125
Cap/Base	E27
Fixture rating	Open
General application	Retail, Residential & Consumer,
Certifications	00
ETIM Class	EC001959
Luminous flux (Im)	1100
Colour temperature (K)	2400
Beam Angle (°)	115
Wattage (W)	17
Product Voltage (V)	230
Average life (Nominal) (h)	25000
IP rating	IP44
Product EAN number	5410288209630

DATA TABLE

General data	
IPC Code	0020963
Product name	SYLGRO
Technology	LED
Watt (Rated) (W)	17
Туре	R125
Cap/Base	E27
Fixture rating	Open
General application	Retail, Residential & Consumer,
Operating temperature rated (°C)	25
Certifications	00
ETIM Class	EC001959




Refled Sylgro SYLGRO 0020963

Optical data	
Luminous flux (Im)	1100
Luminous flux (Rated) (Im)	1100
Photosynthetically active radiation (PAR)	39
Photosynthetic Photon Flux Density (PPFD)	13
Colour temperature (K)	2400
Beam Angle (°)	115
Beam angle (Rated) (°)	115
Electrical data	
Wattage (W)	17
Starting time (max) (s)	0.5
Product Voltage (V)	230
Lamp power factor	0.9
Nominal Frequency (Hz)	50/60Hz
Lifetime data	
Average life (Nominal) (h)	25000
Average life (Rated) (h)	25000
Physical data	
IP rating	IP44
Nominal Product Length (mm)	166
Nominal Product Diameter (mm)	125
Weight (kg)	0.23
Packaging	
Single packaging type	Carton
Product EAN number	5410288209630
Packaging single length / height (cm)	13.1
Packaging single width (cm)	13.1
Packaging single depth (cm)	1.76
DUN14 (outer)	05410288209630
Units per outer package	20
Packaging outer length / height (cm)	68.1
Packaging outer width (cm)	54.3
Packaging outer width (cm) Packaging outer depth (cm)	54.3 38.2
Packaging outer depth (cm)	
Packaging outer depth (cm) Safety data	38.2
Packaging outer depth (cm) Safety data Optimal operating condition (°C)	-40-50
Packaging outer depth (cm) Safety data Optimal operating condition (°C) Special purpose lamp	38.2 -40-50 Yes
Packaging outer depth (cm) Safety data Optimal operating condition (°C) Special purpose lamp Intended purpose	38.2 -40-50 Yes Horticulture
Packaging outer depth (cm) Safety data Optimal operating condition (°C) Special purpose lamp	38.2 -40-50 Yes



Refled Sylgro SYLGRO 0020963

PHOTOMETRY



TECHNICAL DRAWINGS

