

ToLEDo Retro A60

ToLEDo RT GLS V3 CL 806LM 827 E27 BL
0027127



Product features

- Perfect for decorative and general lighting applications and creates a warm ambiance similar to traditional lamps
- Same look, size and functionality as incandescent lamps
- Omni-directional light distribution
- A++ energy rating - up to 134 lm/W
- Suitable for replacement of 60W incandescent lamps
- Gives same sparkling light effect as incandescent lamp
- 90% energy saving
- Dimensionally identical to incandescent lamps - fits all fixtures
- Environment friendly - no mercury and lower CO2 emissions
- Color temperature - 2700K Homelight



PRODUCT OVERVIEW

| | |
|---------------------------------|--------------------------------------|
| IPC Code | 0027127 |
| Product name | ToLEDo RT GLS V3 CL 806LM 827 E27 BL |
| Technology | LED |
| Watt (Rated) (W) | 7 |
| Cap/Base | E27 |
| Fixture rating | Open |
| General application | Hospitality, Residential & Consumer |
| Certifications | EUTIE103 |
| ETIM Class | EC001959 |
| E-number SE | 8295010 |
| Luminous flux (lm) | 806 |
| Colour temperature (K) | 2700 |
| Light colour | Homelight |
| CRI (Ra) | 80 |
| Colour Variation Initial (SDCM) | 6 |
| Colour Consistency (SDCM) | 6 |
| Beam Angle (°) | 300 |
| Wattage (W) | 7 |
| Product Voltage (V) | 230 |
| Average life (Nominal) (h) | 15000 |
| Product EAN number | 5410288271279 |

DATA TABLE

General data

| | |
|----------------------------------|--------------------------------------|
| IPC Code | 0027127 |
| Product name | ToLEDo RT GLS V3 CL 806LM 827 E27 BL |
| Technology | LED |
| Watt (Rated) (W) | 7 |
| Cap/Base | E27 |
| Fixture rating | Open |
| General application | Hospitality, Residential & Consumer |
| Operating temperature rated (°C) | 25 |
| Certifications | EUTIE103 |

ToLEDo Retro A60

ToLEDo RT GLS V3 CL 806LM 827 E27 BL
0027127

| | |
|-------------|----------|
| ETIM Class | EC001959 |
| E-number SE | 8295010 |

Optical data

| | |
|--|-----------|
| Luminous flux (lm) | 806 |
| Luminous flux (Rated) (lm) | 806 |
| Colour temperature (K) | 2700 |
| Light colour | Homelight |
| CRI (Ra) | 80 |
| Colour Variation Initial (SDCM) | 6 |
| Colour Consistency (SDCM) | 6 |
| Adjustable chromaticity | N |
| Beam Angle (°) | 300 |
| Beam angle (Rated) (°) | 300 |
| Lumen maintenance at end of nominal life (%) | 70 |

Electrical data

| | |
|---|---------|
| Wattage (W) | 7 |
| Starting time (max) (s) | 0.5 |
| Warm-up time to 60% of full light (max) (s) | 1 |
| Product Voltage (V) | 230 |
| Lamp power factor | 0.5 |
| No. Of switching cycles before premature failures | 50000 |
| Lamp Energy Label (class) | A++ |
| kWh per 1000 hours burning time | 7 |
| Nominal Frequency (Hz) | 50/60Hz |

Lifetime data

| | |
|----------------------------|-------|
| Average life (Nominal) (h) | 15000 |
| Average life (Rated) (h) | 15000 |

Physical data

| | |
|-------------------------------|-------|
| Nominal Product Length (mm) | 104 |
| Nominal Product Diameter (mm) | 60 |
| Weight (kg) | 0.039 |

Packaging

| | |
|---------------------------------------|---------------------------------|
| Single packaging type | Mix blister(20% carton, 80% pl) |
| Product EAN number | 5410288271279 |
| Packaging single length / height (cm) | 15.2 |
| Packaging single width (cm) | 13.1 |
| Packaging single depth (cm) | 6.2 |
| DUN14 (inner) | 25410288271273 |
| Units per inner package | 6 |
| Packaging inner length / height (cm) | 37.6 |
| Packaging inner width (cm) | 15.9 |
| Packaging inner depth (cm) | 14.5 |

ToLEDo Retro A60

ToLEDo RT GLS V3 CL 806LM 827 E27 BL

0027127

| | |
|--------------------------------------|----------------|
| DUN14 (outer) | 15410288271276 |
| Units per outer package | 60 |
| Packaging outer length / height (cm) | 82.3 |
| Packaging outer width (cm) | 39.2 |
| Packaging outer depth (cm) | 31.3 |

Safety data

| | |
|-------------------------------------|--|
| Breakage cleaning instructions | Not applicable |
| Special purpose lamp | No |
| Intended purpose | No |
| Dry applications use only | Yes |
| Suitable for household illumination | Yes |
| Suitable for accent lighting | Yes |
| Safety message | Not Suitable for totally enclosed fixtures |

