

## ToLEDo Micro-Lynx ToLEDo MicroLynx Clear 250LM 830 0026780



### Product features

- The microlynx LED CLEAR 4W aims to replace a GX53 CFL lamp. This product with a 15,000 hours life is available in 3000 Kelvin color, and will deliver 250lm instantaneously. Perfect for kitchen, under-cabinet walkway or staircase this product is 3 years warranty for a complete peace of mind.



### PRODUCT OVERVIEW

IPC Code	0026780
Product name	ToLEDo MicroLynx Clear 250LM 830
Technology	LED
Watt (Rated) (W)	3
Lamp shape	Micro-Lynx LED
Cap/Base	GX53
Lamp finish	Clear
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Certifications	EUTIE103
ETIM Class	EC001959
E-number FI	4740044
E-number SE	8359420
E-number Norway	3845381
Fixture luminous flux (lm)	RPLA01 : Royalty LED Lamp Single Colour
Luminous flux (lm)	250
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Consistency (SDCM)	6
Wattage (W)	3
Average life (Nominal) (h)	15000
Product EAN number	5410288267807
Chromaticity coordinate Y	-1

### DATA TABLE

#### General data

IPC Code	0026780
Product name	ToLEDo MicroLynx Clear 250LM 830
Technology	LED
Watt (Rated) (W)	3
Lamp shape	Micro-Lynx LED
Cap/Base	GX53

## ToLEDo Micro-Lynx

*ToLEDo MicroLynx Clear 250LM 830*  
0026780

Lamp finish	Clear
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Operating temperature range (°C)	24.5
Certifications	EUTIE103
ETIM Class	EC001959
E-number FI	4740044
E-number SE	8359420
E-number Norway	3845381

### Optical data

Fixture luminous flux (lm)	RPLA01 : Royalty LED Lamp Single Colour
Luminous flux (lm)	250
Luminous flux (Rated) (lm)	250
Rated lamp efficacy 100h HF at 25°C (lm/W)	62.50
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Consistency (SDCM)	6
Adjustable chromaticity	N
Lumen maintenance at end of nominal life (%)	80

### Electrical data

Wattage (W)	3
Equivalent watt (W)	25
Starting time (max) (s)	0.05
Warm-up time to 60% of full light (max) (s)	< 1s => 60%
Current (A)	0.03
Mains voltage (V)	220-240V~
Lamp power factor	0.5
Control gear required	No
No. Of switching cycles before premature failures	>50000
Transformer required	No
Drive current (mA)	21
Lamp Energy Label (class)	A++
Energy efficiency level	A+
kWh per 1000 hours burning time	4

### Lifetime data

Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

### Physical data

Nominal Product Diameter (mm)	25
Max. Lamp Diameter (mm) - D	75
Weight (kg)	0.044

## ToLEDo Micro-Lynx

ToLEDo MicroLynx Clear 250LM 830

0026780


### Packaging

Single packaging type	Carton
Product EAN number	5410288267807
Packaging single length / height (cm)	7.8
Packaging single width (cm)	3.7
Packaging single depth (cm)	7.73
DUN14 (inner)	15410288267804
Units per inner package	6
Packaging inner length / height (cm)	16.5
Packaging inner width (cm)	12.47
Packaging inner depth (cm)	11.0
DUN14 (outer)	35410288267808
Units per outer package	60
Packaging outer length / height (cm)	66.1
Packaging outer width (cm)	18.1
Packaging outer depth (cm)	24.7

### Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Intended purpose	No
Suitable for household illumination	Yes

## TECHNICAL DRAWINGS



Dimensions (mm)

ToLEDo Micro-Lynx  
*ToLEDo MicroLynx Clear 250LM 830*  
0026780

