

ToLEDo Micro-Lynx

ToLEDo MicroLynx Clear 470LM 830 SL
0026784



Product features

- The microlynx LED CLEAR 4W aims to replace a 40W GX53 CFL lamp. This product with a 15,000 hours life is available in 4000 Kelvin color, and will deliver high output of 470lm instantaneously. Perfect for kitchen or bathroom this product is 3 years warranty for a complete peace of mind.



PRODUCT OVERVIEW

IPC Code	0026784
Product name	ToLEDo MicroLynx Clear 470LM 830 SL
Technology	LED
Watt (Rated) (W)	4.5
Lamp shape	Micro-Lynx LED
Cap/Base	GX53
Lamp finish	Clear
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Certifications	EUTIE103
ETIM Class	EC001959
E-number SE	8292214
Fixture luminous flux (lm)	RPLA01 : Royalty LED Lamp Single Colour
Luminous flux (lm)	470
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Consistency (SDCM)	6
Wattage (W)	4.5
Average life (Nominal) (h)	15000
Product EAN number	5410288267845
Chromaticity coordinate Y	-1

DATA TABLE

General data

IPC Code	0026784
Product name	ToLEDo MicroLynx Clear 470LM 830 SL
Technology	LED
Watt (Rated) (W)	4.5
Lamp shape	Micro-Lynx LED
Cap/Base	GX53
Lamp finish	Clear
Fixture rating	Open

ToLEDo Micro-Lynx

ToLEDo MicroLynx Clear 470LM 830 SL
0026784

General application	Hospitality, Residential & Consumer
Operating temperature range (°C)	24.6
Certifications	EUTIE103
ETIM Class	EC001959
E-number SE	8292214

Optical data

Fixture luminous flux (lm)	RPLA01 : Royalty LED Lamp Single Colour
Luminous flux (lm)	470
Luminous flux (Rated) (lm)	470
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Consistency (SDCM)	6
Adjustable chromaticity	N
Lumen maintenance at end of nominal life (%)	80

Electrical data

Wattage (W)	4.5
Equivalent watt (W)	40
Starting time (max) (s)	0.05
Warm-up time to 60% of full light (max) (s)	< 1s => 60%
Current (A)	0.052
Mains voltage (V)	220-240V~
Lamp power factor	0.4
Control gear required	No
No. Of switching cycles before premature failures	50000
Transformer required	No
Drive current (mA)	35
Lamp Energy Label (class)	A++
Energy efficiency level	A++
kWh per 1000 hours burning time	5

Lifetime data

Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

Physical data

Nominal Product Diameter (mm)	25
Max. Lamp Diameter (mm) - D	75
Weight (kg)	0.045

Packaging

Single packaging type	Carton
Product EAN number	5410288267845
Packaging single length / height (cm)	7.8
Packaging single width (cm)	3.8

ToLEDo Micro-Lynx


ToLEDo MicroLynx Clear 470LM 830 SL

0026784

Packaging single depth (cm)	7.8
DUN14 (inner)	25410288267849
Units per inner package	6
Packaging inner length / height (cm)	16.3
Packaging inner width (cm)	12.4
Packaging inner depth (cm)	10.5
DUN14 (outer)	15410288267842
Units per outer package	60
Packaging outer length / height (cm)	66.0
Packaging outer width (cm)	18.2
Packaging outer depth (cm)	25.0

Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Intended purpose	General lighting
Suitable for household illumination	Yes





ToLEDo Micro-Lynx

ToLEDo MicroLynx Clear 470LM 830 SL

0026784
