

## ToLEDo Micro-Lynx

ToLEDo MicroLynx Frosted 470LM 840 SL

0026787



### Product features

- The microlynx LED FROSTED 4W aims to replace a GX53 CFL lamp. This product with a 15,000 hours life is available in 4000 Kelvin color, and will deliver high output of 470lm instantaneously. Perfect for kitchen or bathroom this product is 3 years warranty for a complete peace of mind.



## PRODUCT OVERVIEW

IPC Code	0026787
Product name	ToLEDo MicroLynx Frosted 470LM 840 SL
Technology	LED
Watt (Rated) (W)	4.5
Lamp shape	Micro-Lynx LED
Cap/Base	GX53
Lamp finish	frosted
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Certifications	EUTIE103
ETIM Class	EC001959
E-number FI	4740349
E-number SE	8292211
Fixture luminous flux (lm)	RPLA01 : Royalty LED Lamp Single Colour
Luminous flux (lm)	470
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Consistency (SDCM)	6
Wattage (W)	4.5
Average life (Nominal) (h)	15000
Product EAN number	5410288267876
Chromaticity coordinate Y	-1

## DATA TABLE

### General data

IPC Code	0026787
Product name	ToLEDo MicroLynx Frosted 470LM 840 SL
Technology	LED
Watt (Rated) (W)	4.5
Lamp shape	Micro-Lynx LED
Cap/Base	GX53
Lamp finish	frosted

## ToLEDo Micro-Lynx

ToLEDo MicroLynx Frosted 470LM 840 SL

0026787

Fixture rating	Open
General application	Hospitality, Residential & Consumer
Operating temperature range (°C)	24.6
Certifications	EUTIE103
ETIM Class	EC001959
E-number FI	4740349
E-number SE	8292211

### Optical data

Fixture luminous flux (lm)	RPLA01 : Royalty LED Lamp Single Colour
Luminous flux (lm)	470
Luminous flux (Rated) (lm)	470
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Consistency (SDCM)	6
Adjustable chromaticity	N
Lumen maintenance at end of nominal life (%)	80

### Electrical data

Wattage (W)	4.5
Equivalent watt (W)	40
Starting time (max) (s)	0.05
Warm-up time to 60% of full light (max) (s)	< 1s => 60%
Current (A)	0.052
Mains voltage (V)	220-240V~
Lamp power factor	0.4
Control gear required	No
No. Of switching cycles before premature failures	50000
Transformer required	No
Drive current (mA)	35
Lamp Energy Label (class)	A++
Energy efficiency level	A++
kWh per 1000 hours burning time	5

### Lifetime data

Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

### Physical data

Nominal Product Diameter (mm)	25
Max. Lamp Diameter (mm) - D	75
Weight (kg)	0.045

### Packaging

Single packaging type	Carton
Product EAN number	5410288267876

## ToLEDo Micro-Lynx

*ToLEDo MicroLynx Frosted 470LM 840 SL*

0026787

Packaging single length / height (cm)	7.8
Packaging single width (cm)	3.8
Packaging single depth (cm)	7.8
DUN14 (inner)	25410288267870
Units per inner package	6
Packaging inner length / height (cm)	16.3
Packaging inner width (cm)	12.4
Packaging inner depth (cm)	10.5
DUN14 (outer)	15410288267873
Units per outer package	60
Packaging outer length / height (cm)	66.0
Packaging outer width (cm)	18.2
Packaging outer depth (cm)	25.0

### Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Intended purpose	General lighting
Suitable for household illumination	Yes

## ToLEDo Micro-Lynx

ToLEDo MicroLynx Frosted 470LM 840 SL  
0026787

