

Ascent 150 II Square

ASCENT 150 II SQ 2300 3K DALI
2059397



Product features

- The ASCENT 150 II SQ 2300 3K DALI is a high efficient downlight luminaire with luminous flux: 2322lm, luminaire efficacy: 122lm/W, Colour rendering index Ra >80, Colour temperature: 3000K Warm white, Average life rated at 50,000Hrs, Class II, Protection rating IP44/IK02, Cut out dimensions: 175mm, Weight: 1.7kg



PRODUCT OVERVIEW

IPC Code	2059397
Product name	ASCENT 150 II SQ 2300 3K DALI
Technology	LED
Housing	Aluminium
Mount	Recessed
Environment	Internal
General application	Hospitality,Office,Retail
Certifications	EUNEW008
ETIM Class	EC001744
E-number FI	4237809
Fixture luminous flux (lm)	2322
Luminaire efficacy (lm/W)	122
LOR (%)	100
Colour temperature (K)	3000
CRI (Ra)	80
Colour Consistency (SDCM)	3
Photobiological Risk Group	Exempt Group 0
Total power consumption (W)	19
Electrical protection	Class II
Control gear type	Electronic
Minimum dimming level (%)	99
Average life (Nominal) (h)	50000
IP rating	IP44
IK rating	IK02
Product EAN number	5025768593972
Included lamp	INTEGRATED LED

DATA TABLE

General data

IPC Code	2059397
Product name	ASCENT 150 II SQ 2300 3K DALI
Technology	LED
Housing	Aluminium
Mount	Recessed

Ascent 150 II Square

ASCENT 150 II SQ 2300 3K DALI
2059397

Environment	Internal
General application	Hospitality, Office, Retail
Certifications	EUNEW008
ETIM Class	EC001744
E-number FI	4237809

Optical data

Fixture luminous flux (lm)	2322
Luminaire efficacy (lm/W)	122
LOR (%)	100
Colour temperature (K)	3000
CRI (Ra)	80
Colour Consistency (SDCM)	3
Adjustable chromaticity	N
Beam angle (Rated) (°)	80
Distribution type	Direct
Photobiological Risk Group	Exempt Group 0

Electrical data

Total power consumption (W)	19
Mains voltage (V)	220-240V~
Electrical protection	Class II
Control gear type	Electronic
Transformer required	Yes
Minimum dimming level (%)	99
Inrush Current (A)	20.9
Inrush Duration (µs)	139
Glow Wire Test (°C)	650
Nominal Frequency (Hz)	50/60/HF
Max. Luminaires per 16A C Breaker	48

Lifetime data

Lumen maintenance - L70 B50	60000
Lumen maintenance - L70 B20	60000
Lumen maintenance - L70 B10	60000
Lumen maintenance - L80 B50	60000
Lumen maintenance - L80 B20	60000
Lumen maintenance - L80 B10	60000
Lumen maintenance - L90 B50	60000
Lumen maintenance - L90 B20	60000
Lumen maintenance - L90 B10	52000
Average life (Nominal) (h)	50000

Physical data

IP rating	IP44
IK rating	IK02
Diffuser finish	Clear
Nominal Product Width (mm)	188
Nominal Product Height (mm)	158

Ascent 150 II Square

ASCENT 150 II SQ 2300 3K DALI
2059397

Weight (kg)	1.7
Recessed Depth (mm)	158

Packaging


Single packaging type	Carton
Product EAN number	5025768593972
Packaging single length / height (cm)	25.0
Packaging single width (cm)	20.0
Packaging single depth (cm)	25.0
DUN14 (outer)	05025768593972
Units per outer package	1
Packaging outer length / height (cm)	25.0
Packaging outer width (cm)	20.0
Packaging outer depth (cm)	25.0

PHOTOMETRY


0.5	1.03	E(0°) E(C0)	45.8°	3873 827
1.0	2.06	E(0°) E(C0)	45.8°	968 207
1.5	3.08	E(0°) E(C0)	45.8°	430 92
2.0	4.11	E(0°) E(C0)	45.8°	242 52
2.5	5.14	E(0°) E(C0)	45.8°	155 33
3.0	6.17	E(0°) E(C0)	45.8°	108 23

Distance [m] Cone diameter [m] Illuminance [lx]

— C0 - C180 (Half beam angle: 91.6°)



TECHNICAL DRAWINGS



Ascent 150 II Square

ASCENT 150 II SQ 2300 3K DALI
2059397

