

Ascent 150 II Round Office

ASCENT 150 II OFFICE 3K DALI

2059445



Product features

- The Ascent 150 II Office 3K DALI is a high efficient downlight luminaire with luminous flux: 2052lm, luminaire efficacy: 93lm/W, Colour rendering index Ra >80, Colour temperature: 3000K Warm white, Average life rated at 50,000Hrs, Class II, Protection rating IP44/IK02, UGR <19 according to EN12464-1 for indoor work places, Cut out dimensions: 176mm, Weight: 1.7kg



PRODUCT OVERVIEW

IPC Code	2059445
Product name	ASCENT 150 II OFFICE 3K DALI
Technology	LED
Housing	Aluminium
Mount	Recessed
Environment	Internal
General application	Hospitality,Office,Retail
Certifications	EUNEW008
ETIM Class	EC001744
Fixture luminous flux (lm)	2052
Luminaire efficacy (lm/W)	93
LOR (%)	100
Colour temperature (K)	3000
CRI (Ra)	80
Colour Consistency (SDCM)	3
Glare control	UGR <19
Photobiological Risk Group	Exempt Group 0
Total power consumption (W)	22
Electrical protection	Class II
Control gear type	Electronic
Minimum dimming level (%)	99
Average life (Nominal) (h)	50000
IP rating	IP44
IK rating	IK02
Product EAN number	5025768594450
Included lamp	INTEGRATED LED

DATA TABLE

General data

IPC Code	2059445
Product name	ASCENT 150 II OFFICE 3K DALI
Technology	LED
Housing	Aluminium
Mount	Recessed

Ascent 150 II Round Office

ASCENT 150 II OFFICE 3K DALI
2059445

Environment	Internal
General application	Hospitality, Office, Retail
Certifications	EUNEW008
ETIM Class	EC001744

Optical data

Fixture luminous flux (lm)	2052
Luminaire efficacy (lm/W)	93
LOR (%)	100
Colour temperature (K)	3000
CRI (Ra)	80
Colour Consistency (SDCM)	3
Adjustable chromaticity	N
Beam angle (Rated) (°)	80
Distribution type	Direct
Glare control	UGR <19
Photobiological Risk Group	Exempt Group 0

Electrical data

Total power consumption (W)	22
Mains voltage (V)	220-240V~
Electrical protection	Class II
Control gear type	Electronic
Transformer required	Yes
Minimum dimming level (%)	99
Inrush Current (A)	20.9
Inrush Duration (µs)	139
Glow Wire Test (°C)	650
Nominal Frequency (Hz)	50/60/HF
Max. Luminaires per 16A C Breaker	48

Lifetime data

Lumen maintenance - L70 B50	60000
Lumen maintenance - L70 B20	60000
Lumen maintenance - L70 B10	60000
Lumen maintenance - L80 B50	60000
Lumen maintenance - L80 B20	60000
Lumen maintenance - L80 B10	60000
Lumen maintenance - L90 B50	60000
Lumen maintenance - L90 B20	60000
Lumen maintenance - L90 B10	52000
Average life (Nominal) (h)	50000

Physical data

IP rating	IP44
IK rating	IK02
Diffuser finish	Microprismatic
Nominal Product Width (mm)	189
Nominal Product Height (mm)	142

Ascent 150 II Round Office


ASCENT 150 II OFFICE 3K DALI
2059445

Weight (kg)	1.75
Recessed Depth (mm)	142

Packaging

Single packaging type	Carton
Product EAN number	5025768594450
Packaging single length / height (cm)	25.0
Packaging single width (cm)	20.0
Packaging single depth (cm)	25.0
DUN14 (outer)	05025768594450
Units per outer package	1
Packaging outer length / height (cm)	25.0
Packaging outer width (cm)	20.0
Packaging outer depth (cm)	25.0

PHOTOMETRY



Distance [m]	Cone diameter [m]	Beam diameter [m]	Beam angle [°]	Illuminance [lx]
0.5	0.00	0.00	0.0°	646
1.0	0.00	0.00	0.0°	1314
1.5	0.00	0.00	0.0°	611
2.0	0.00	0.00	0.0°	343
2.5	0.00	0.00	0.0°	220
3.0	0.00	0.00	0.0°	153

Distance [m] Cone diameter [m] Beam diameter [m] Beam angle [°] Illuminance [lx]
C0 - C180 (Half beam angle: 0.0°)

Ascent 150 II Round Office ASCENT 150 II OFFICE 3K DALI 2059445

