

Aquastar T8 F25W/30Aquastar Retail 0000645



Product features

Colour temperature 10,000K recreating the tropical light spectrum. For fresh and marine aquariums. Excellent combination with DaylighStar. Outsanding results in combination with Daylightstar.

















PRODUCT OVERVIEW

| IPC Code | 0000645 |
|----------------------------|---|
| Product name | F25W/30Aquastar Retail |
| Technology | Fluorescent |
| Watt (Rated) (W) | 26.00 |
| Lamp shape | Tubular |
| Type | T8 |
| Cap/Base | G13 |
| Lamp finish | Coated |
| Fixture rating | Open |
| General application | Hospitality,Retail,Residential & Consumer |
| Certifications | 00 |
| ETIM Class | EC000108 |
| Luminous flux (Im) | 1500 |
| Colour temperature (K) | 10000 |
| Light colour | Aquastar |
| Wattage (W) | 25.00 |
| Product Voltage (V) | 84 |
| Dimmable | Yes |
| Average life (Nominal) (h) | 10000 |
| Product EAN number | 5410288006451 |

DATA TABLE

| General data | |
|--------------|------------------------|
| IPC Code | 0000645 |
| Product name | F25W/30Aquastar Retail |



Aquastar T8 F25W/30Aquastar Retail 0000645

| Technology | Fluorescent |
|---------------------------------------|---|
| Watt (Rated) (W) | 26.00 |
| Lamp shape | Tubular |
| Туре | Т8 |
| Cap/Base | G13 |
| Lamp finish | Coated |
| Fixture rating | Open |
| General application | Hospitality, Retail, Residential & Consumer |
| Operating temperature range (°C) | -15°C to +40°C |
| Certifications | 00 |
| ETIM Class | EC000108 |
| | |
| Optical data | |
| Luminous flux (lm) | 1500 |
| Ambient temperature for maximum | 25 |
| luminous flux (°C) | 25 |
| Colour temperature (K) | 10000 |
| Light colour | Aquastar |
| Adjustable chromaticity | N |
| | |
| Electrical data | |
| Wattage (W) | 25.00 |
| Watt (Rated) - High frequency (W) | 24.50 |
| Current (A) | 0.360 |
| Product Voltage (V) | 84 |
| Control gear required | Yes |
| Transformer required | No |
| Dimmable | Yes |
| Drive current (mA) | 360 |
| , | |
| Lifetime data | |
| Average life (Nominal) (h) | 10000 |
| Average life (Rated) (h) | 10000 |
| 3 (, () | |
| Physical data | |
| Nominal Product Length (mm) | 750.0 |
| Nominal Product Diameter (mm) | 26 |
| Max. Length base to base (mm) - A | 742.2 |
| Length base to pin Min-Max (mm) - B | 746.9-749.3 |
| Max. Lamp Length (mm) - C/L | 756.4 |
| Max. Lamp Diameter (mm) - D | 28.0 |
| Weight (kg) | 0.102 |
| MeiRiff (VA) | 0.102 |
| Packaging | |
| Single packaging type | Carton |
| Product EAN number | 5410288006451 |
| Packaging single length / height (cm) | 82.5 |
| Packaging single width (cm) | 2.7 |
| | |
| Packaging single depth (cm) | 2.7 |



Aquastar T8 F25W/30Aquastar Retail 0000645

| DUN14 (outer) | 15410288006458 |
|--------------------------------------|--------------------------------|
| Units per outer package | 10 |
| Packaging outer length / height (cm) | 85.5 |
| Packaging outer width (cm) | 6.5 |
| Packaging outer depth (cm) | 14.7 |
| Safety data | |
| Lamp mercury content (mg) | 2.80 |
| Breakage cleaning instructions | Applicable |
| Special purpose lamp | Yes |
| Intended purpose | Fresh / Marine water aquariums |
| Suitable for household illumination | No |

Not suitable for household

TECHNICAL DRAWINGS

Safety message

