Ascent 150 II Round White Reflector

ASCENT 150 II 3100 4K DALIEM WHT

2059450



Product features

- The ASCENT150II 3100 4K DALIEM WHT is a high efficient downlight luminaire with luminous flux: 3403, luminaire efficacy: 121.535714285714, Colour rendering index Ra >80, Colour temperature: 4000K Neutral White, Average life rated at 50,000Hrs, Class II, Protection rating IP44/IK02, Cut out dimensions: 176mm, Weight: 2.45kg

PRODUCT OVERVIEW

IPC Code	2059450
Product name	ASCENT 150 II 3100 4K DALIEM WHT
Technology	LED
Housing	Aluminium
Mount	Recessed
Environment	Internal
General application	Hospitality,Office,Retail
Certifications	EUNEW001
ETIM Class	EC001744
Fixture luminous flux (lm)	3403
Luminaire efficacy (lm/W)	122
LOR (%)	100
Colour temperature (K)	4000
CRI (Ra)	80
Colour Consistency (SDCM)	3
Photobiological Risk Group	Exempt Group 0
Total power consumption (W)	28
Electrical protection	Class II
Control gear type	Electronic
Minimum dimming level (%)	99
Average life (Nominal) (h)	50000
IP rating	IP44
IK rating	IK02
Product EAN number	5025768594504
Included lamp	INTEGRATED LED

DATA TABLE

General data

IPC Code	2059450
Product name	ASCENT 150 II 3100 4K DALIEM WHT
Technology	LED
Housing	Aluminium
Mount	Recessed
Environment	Internal

© Feilo Sylvania | Date Printed: 27 Dec 2018

Ascent 150 II Round White Reflector

ASCENT 150 II 3100 4K DALIEM WHT

2059450

General application	Hospitality,Office,Retail
Certifications	EUNEW001
ETIM Class	EC001744

Optical data

Fixture luminous flux (lm)	3403
Luminaire efficacy (lm/W)	122
LOR (%)	100
Colour temperature (K)	4000
CRI (Ra)	80
Colour Consistency (SDCM)	3
Adjustable chromaticity	N
Beam angle (Rated) (°)	80
Distribution type	Direct
Photobiological Risk Group	Exempt Group 0

Electrical data

Total power consumption (W)	28
Mains voltage (V)	230-240V~
Electrical protection	Class II
Control gear type	Electronic
Minimum dimming level (%)	99
Drive current (mA)	1000
Inrush Current (A)	20.9
Inrush Duration (µs)	139
Glow Wire Test (°C)	650
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 16A C Breaker	48

Lifetime data

Lumen maintenance - L70 B50	60000
Lumen maintenance - L70 B20	60000
Lumen maintenance - L70 B10	60000
Lumen maintenance - L80 B50	60000
Lumen maintenance - L80 B20	60000
Lumen maintenance - L80 B10	60000
Lumen maintenance - L90 B50	60000
Lumen maintenance - L90 B20	60000
Lumen maintenance - L90 B10	52000
Average life (Nominal) (h)	50000

Physical data

IP rating	IP44
IK rating	IK02
Diffuser finish	Clear
Nominal Product Width (mm)	189
Nominal Product Height (mm)	142
Weight (kg)	2.45
Recessed Depth (mm)	142

© Feilo Sylvania | Date Printed: 27 Dec 2018


Ascent 150 II Round White Reflector

ASCENT 150 II 3100 4K DALIEM WHT

2059450

Packaging

Single packaging type	Carton
Product EAN number	5025768594504
Packaging single length / height (cm)	25.0
Packaging single width (cm)	20.0
Packaging single depth (cm)	25.0
DUN14 (outer)	05025768594504
Units per outer package	1
Packaging outer length / height (cm)	25.0
Packaging outer width (cm)	20.0
Packaging outer depth (cm)	25.0




© Feilo Sylvania | Date Printed: 27 Dec 2018

Ascent 150 II Round White Reflector

ASCENT 150 II 3100 4K DALIEM WHT

2059450



© Feilo Sylvania | Date Printed: 27 Dec 2018