

Start Waterproof LED G3 DALI

START WATERPROOF LED G3 1500MM T 4K QC DALI

0048659



Product features

- Start Waterproof, integrated LED weatherproof luminaire, with UV stabilized flat diffuser and linear prisms designed to achieve uniform lit appearance, optimise light output and to reduce glare, stainless steel diffuser clips and fixing brackets for surface mounting. Polycarbonate housing, Polycarbonate diffuser, 7300lm, 58W, 126lm/W, 4000K, drive current 1050mA, DALI dimmable, with quick connector, CRI80, IP65, IK08, Class I, nominal average life (h):50000, 1578mm x 110mm x 78mm ,energy class: A++ A+ A



PRODUCT OVERVIEW

IPC Code	0048659
Product name	START WATERPROOF LED G3 1500MM T 4K QC DALI
Technology	LED
Housing	Polycarbonate
Mount	Ceiling Mounting and Suspended Mounting
Fixture rating	Enclosed
General application	Logistics & Industry
Certifications	EUNEW009
ETIM Class	EC002892
E-number SE	7214456
Fixture luminous flux (lm)	7300
Luminaire efficacy (lm/W)	126
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	100
Glare control	25.6
Photobiological Risk Group	RG0
Total power consumption (W)	58
Electrical protection	Class I
Control gear type	Electronic dimmable DALI
Dimmable	Yes
Minimum dimming level (%)	1
LED Flickering Rate	Ultra low (5% or less)
Average life (Nominal) (h)	50000
Housing colour	Grey
IP rating	IP65
IK rating	IK08
Product EAN number	5410288486598
Lamps	Yes
Included lamp	INTEGRATED LED

Start Waterproof LED G3 DALI

START WATERPROOF LED G3 1500MM T 4K QC DALI
0048659

DATA TABLE

General data

IPC Code	0048659
Product name	START WATERPROOF LED G3 1500MM T 4K QC DALI
Technology	LED
Housing	Polycarbonate
Mount	Ceiling Mounting and Suspended Mounting
Fixture rating	Enclosed
General application	Logistics & Industry
Operating temperature range (°C)	-20°C to +40°C
Certifications	EUNEW009
ETIM Class	EC002892
E-number SE	7214456

Optical data

Fixture luminous flux (lm)	7300
Luminaire efficacy (lm/W)	126
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	3
Beam Angle (°)	100
Distribution type	Direct
Glare control	25.6
Photobiological Risk Group	RG0

Electrical data

Total power consumption (W)	58
Mains voltage (V)	220-240V~
THD (at 230 V, 50 Hz, full load, at 100% dimming level) xx.x %	16.0
Mains frequency (Hz)	0/50/60Hz
Electrical protection	Class I
Control gear required	No
Control gear type	Electronic dimmable DALI
Dimmable	Yes
Minimum dimming level (%)	1
Drive current (mA)	1050
Inrush Current (A)	40
Inrush Duration (µs)	178
Glow Wire Test (°C)	850
Nominal Frequency (Hz)	DC/50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. Luminaires per 10A C Breaker	15
Max. Luminaires per 13A C Breaker	20
Max. Luminaires per 16A C Breaker	23
Max. Luminaires per 20A C Breaker	30
Max. Luminaires per 10A B Breaker	9

Start Waterproof LED G3 DALI

START WATERPROOF LED G3 1500MM T 4K QC DALI

0048659

Max. Luminaires per 13A B Breaker	12
Max. Luminaires per 16A B Breaker	14
Max. Luminaires per 20A B Breaker	18

Lifetime data

Lumen maintenance - L70 B50	60000
Lumen maintenance - L70 B20	60000
Lumen maintenance - L70 B10	60000
Lumen maintenance - L80 B50	60000
Lumen maintenance - L80 B20	60000
Lumen maintenance - L80 B10	60000
Lumen maintenance - L90 B50	59000
Lumen maintenance - L90 B20	53000
Lumen maintenance - L90 B10	50000
Average life (Nominal) (h)	50000

Physical data

Housing colour	Grey
IP rating	IP65
IK rating	IK08
Diffuser finish	Clear
Diffuser material	Polycarbonate
Nominal Product Length (mm)	1578
Nominal Product Width (mm)	110
Nominal Product Height (mm)	78
Weight (kg)	2.46

Packaging


Single packaging type	Carton
Product EAN number	5410288486598
Packaging single length / height (cm)	167.2
Packaging single width (cm)	11.6
Packaging single depth (cm)	8.4
DUN14 (outer)	05410288486598
Units per outer package	1
Packaging outer length / height (cm)	167.2
Packaging outer width (cm)	11.6
Packaging outer depth (cm)	8.4

Safety data

Dry applications use only	No
---------------------------	----

PHOTOMETRY

Start Waterproof LED G3 DALI START WATERPROOF LED G3 1500MM T 4K QC DALI 0048659



Distance [m]	Cone diameter [m]	illuminance [lx]
0.5	1.15 1.62	E(U) 49.0° 946 E(C90) 134 E(C0) 58.3° 690
1.0	2.30 3.24	E(U) 2374 E(C90) 49.0° 338 E(C0) 58.3° 173
1.5	3.45 4.86	E(U) 1085 E(C90) 49.0° 149 E(C0) 58.3° 77
2.0	4.60 6.48	E(U) 594 E(C90) 49.0° 84 E(C0) 58.3° 43
2.5	5.75 8.10	E(U) 390 E(C90) 49.0° 64 E(C0) 58.3° 33
3.0	6.90 9.71	E(U) 284 E(C90) 49.0° 51 E(C0) 58.3° 26

Distance [m] Cone diameter [m] illuminance [lx]
 C0 - C180 (Half beam angle: 116.6°)
 C90 - C270 (Half beam angle: 58.3°)

TECHNICAL DRAWINGS



SYLVANIA 0048659

This luminaire contains built in LED lamps.

A++
A+
A
B
C
D
E

}

LED

The lamps cannot be changed in the luminaire.

874/2012

Start Waterproof LED G3 DALI


START WATERPROOF LED G3 1500MM T 4K QC DALI

0048659



This luminaire contains built in LED lamps.

The lamps cannot be changed in the luminaire.



SYLVANIA 0048659 874/2012