

START eco Flood Flat PIR

START eco Flood Flat IP54 PIR 4500lm 840

0047971



Product features

- The new Start eco Flood Flat comes with improved design. The streamlined, durable, lightweight die-cast aluminium body makes it a perfect choice for building facades, car parks, garages and construction areas. The product includes 1 m pre-wired stripped cable and fitting bracket for quick and easy installation and the universal mounting bracket allows wall or surface mounting with the possibility of vertical tilting. Black die-cast aluminum housing, white reflector, 4750 lm, 51 W, 93 lm/W, 4000K, drive current 193 mA, non dimmable, CRI>80, IP54, IK07 - fixture, IK05 - sensor, Class I, lumen maintenance L70:B50: 30000 hrs, 193 x 216 x 70 mm (L x W x H). Weight: 0.85kg. PIR sensor included. Energy class: A++ A+ A.



PRODUCT OVERVIEW

IPC Code	0047971
Product name	START eco Flood Flat IP54 PIR 4500lm 840
Technology	LED
Housing	ADC12
General application	Residential & Consumer
Certifications	EUNEW005
ETIM Class	EC001744
E-number FI	4579438
Fixture luminous flux (lm)	4750
Luminaire efficacy (lm/W)	93
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Beam Angle (°)	110
Photobiological Risk Group	RG1
Total power consumption (W)	51
Electrical protection	Class I
Housing colour	RAL9017
IP rating	IP54
IK rating	IK05
Product EAN number	5410288479712
Lamps	No

DATA TABLE

General data

IPC Code	0047971
Product name	START eco Flood Flat IP54 PIR 4500lm 840
Technology	LED
Housing	ADC12
General application	Residential & Consumer
Operating temperature range (°C)	-20°C~+40°C
Certifications	EUNEW005
ETIM Class	EC001744

START eco Flood Flat PIR

START eco Flood Flat IP54 PIR 4500lm 840

0047971

E-number FI	4579438
-------------	---------

Optical data

Fixture luminous flux (lm)	4750
Luminaire efficacy (lm/W)	93
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Beam Angle (°)	110
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	51
Mains voltage (V)	220-240V~
Lamp power factor	0.9
Electrical protection	Class I
Drive current (mA)	193
Inrush Current (A)	19.8
Inrush Duration (µs)	590
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 10A C Breaker	13
Max. Luminaires per 13A C Breaker	18
Max. Luminaires per 16A C Breaker	22
Max. Luminaires per 20A C Breaker	27
Max. Luminaires per 10A B Breaker	6
Max. Luminaires per 13A B Breaker	9
Max. Luminaires per 16A B Breaker	11
Max. Luminaires per 20A B Breaker	14

Lifetime data

Lumen maintenance - L70 B50	30000
-----------------------------	-------

Physical data

Housing colour	RAL9017
IP rating	IP54
IK rating	IK05
Nominal Product Length (mm)	193
Nominal Product Width (mm)	216
Nominal Product Height (mm)	70
Weight (kg)	0.85


Packaging

Single packaging type	Carton
Product EAN number	5410288479712
Packaging single length / height (cm)	19.6
Packaging single width (cm)	9.6
Packaging single depth (cm)	21.8
DUN14 (outer)	15410288479719
Units per outer package	5


START eco Flood Flat PIR
START eco Flood Flat IP54 PIR 4500lm 840
0047971

Packaging outer length / height (cm)	50.2
Packaging outer width (cm)	21.6
Packaging outer depth (cm)	25.1

PHOTOMETRY



TECHNICAL DRAWINGS



START eco Flood Flat PIR

START eco Flood Flat IP54 PIR 4500lm 840

0047971

