

Start Waterproof Housing

START WATERPROOF 1200 HOUSING 2X

0047923



Product features

- Luminaire, polycarbonate housing • Twin version, 1200mm • Protection type IP65 • Luminous flux and light colour vary depending on LED tubes used • To be used with T8 LED tubes • Easy to install with stainless steel fixing brackets included for ceiling mounting • Ideal for any industrial facilities, garages, car parks, workshops.



PRODUCT OVERVIEW

IPC Code	0047923
Product name	START WATERPROOF 1200 HOUSING 2X
Technology	LED
Type	na
Housing	Polycarbonate
Mount	Surface
General application	Logistics & Industry
Certifications	00
ETIM Class	EC002892
LOR (%)	75
Electrical protection	Class I
Housing colour	Grey
IP rating	IP65
IK rating	IK08
Product EAN number	5410288479231
Lamps	No

DATA TABLE

General data

IPC Code	0047923
Product name	START WATERPROOF 1200 HOUSING 2X
Technology	LED
Type	na
Housing	Polycarbonate
Mount	Surface
General application	Logistics & Industry
Certifications	00
ETIM Class	EC002892

Optical data

LOR (%)	75
Distribution type	Direct

Start Waterproof Housing

START WATERPROOF 1200 HOUSING 2X
0047923

Electrical data

Electrical protection	Class I
Glow Wire Test (°C)	650

Physical data

Housing colour	Grey
IP rating	IP65
IK rating	IK08
Diffuser finish	Clear
Diffuser material	Polycarbonate
Nominal Product Length (mm)	1260
Nominal Product Width (mm)	99
Nominal Product Height (mm)	78
Weight (kg)	1.11

Packaging

Single packaging type	Carton
Product EAN number	5410288479231
Packaging single length / height (cm)	128.0
Packaging single width (cm)	9.9
Packaging single depth (cm)	5.2
DUN14 (outer)	15410288479238
Units per outer package	1
Packaging outer length / height (cm)	128.0
Packaging outer width (cm)	9.9
Packaging outer depth (cm)	5.2

TECHNICAL DRAWINGS

