Start Batten IP65

START BATTEN IP65 48W 1500 3K

0045156



Product features

- The new upgraded Start Batten IP65 (upgraded version of Batten LED LINK) is a versatile range of slimline LED waterproof luminaires that provide an ideal solution for interior and exterior applications such as workshops, garages and outdoor covered spaces. The design allows the luminaire to be easily linked to another luminaire through an IP65 rated connector. The product can be a slimline replacement for single and twin 36W/58W fluorescent waterproof battens.Polycarbonate housing and diffuser, 6000 lm, 48 W, 125 lm/W, 4000 K, drive current 300 mA, non dimmable, CRI 80, IP65, IK08, Class II, nominal average lifetime (h): 30000, 1500 mm x 80 mm x 53.6 mm, energy class: A++ A+ A.

PRODUCT OVERVIEW

IPC Code	0045156
Product name	START BATTEN IP65 48W 1500 3K
Technology	LED
Housing	Polycarbonate
Mount	Surface Mounted
Fixture rating	Enclosed
General application	Residential & Consumer
Certifications	EUNEW009
ETIM Class	EC000109
E-number FI	4274235
E-number SE	7214468
Fixture luminous flux (lm)	5520
Luminaire efficacy (lm/W)	115
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Beam Angle (°)	120
Glare control	25.1
Photobiological Risk Group	RG0
Total power consumption (W)	48
Electrical protection	Class II
Control gear type	Electronic (constant current)
Dimmable	No
LED Flickering Rate	Ultra low (5% or less)
Average life (Nominal) (h)	30000
Housing colour	White
IP rating	IP65
IK rating	IK08
Product EAN number	5410288451565
Lamps	Yes
Included lamp	INTEGRATED LED

© Feilo Sylvania | Date Printed: 28 Dec 2018

Start Batten IP65

START BATTEN IP65 48W 1500 3K

0045156

DATA TABLE

General data

IPC Code	0045156
Product name	START BATTEN IP65 48W 1500 3K
Technology	LED
Housing	Polycarbonate
Mount	Surface Mounted
Fixture rating	Enclosed
General application	Residential & Consumer
Operating temperature range (°C)	-10 to +40
Certifications	EUNEW009
ETIM Class	EC000109
E-number FI	4274235
E-number SE	7214468

Optical data

Fixture luminous flux (lm)	5520
Luminaire efficacy (lm/W)	115
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Beam Angle (°)	120
Distribution type	Direct
Glare control	25.1
Photobiological Risk Group	RG0

Electrical data

Total power consumption (W)	48
Mains voltage (V)	220-240V~
Lamp power factor	0.9
Electrical protection	Class II
Control gear type	Electronic (constant current)
Dimmable	No
Drive current (mA)	300
Inrush Current (A)	16
Inrush Duration (µs)	250
Glow Wire Test (°C)	650
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. Luminaires per 10A C Breaker	28
Max. Luminaires per 13A C Breaker	37
Max. Luminaires per 16A C Breaker	47
Max. Luminaires per 20A C Breaker	58

Lifetime data

Lumen maintenance - L70 B50	30000

© Feilo Sylvania | Date Printed: 28 Dec 2018

Start Batten IP65

START BATTEN IP65 48W 1500 3K

0045156

Average life (Nominal) (h)	30000


Physical data


Housing colour	White
IP rating	IP65
IK rating	IK08
Diffuser finish	Opaque
Diffuser material	Polycarbonate
Nominal Product Length (mm)	1500
Nominal Product Width (mm)	80
Nominal Product Height (mm)	53.6
Weight (kg)	1.354

Packaging


Single packaging type	Carton
Product EAN number	5410288451565
Packaging single length / height (cm)	159.5
Packaging single width (cm)	9.93
Packaging single depth (cm)	6.63
DUN14 (outer)	15410288451562
Units per outer package	9
Packaging outer length / height (cm)	160.7
Packaging outer width (cm)	32.1
Packaging outer depth (cm)	22.1

PHOTOMETRY





TECHNICAL DRAWINGS





© Feilo Sylvania | Date Printed: 28 Dec 2018

Start Batten IP65

START BATTEN IP65 48W 1500 3K

0045156





© Feilo Sylvania | Date Printed: 28 Dec 2018