

## Start Tubular - Electronic

*Start Tubular IP66 114 EB 840*

0042300



### PRODUCT OVERVIEW

IPC Code	0042300
Product name	Start Tubular IP66 114 EB 840
Technology	Fluorescent
Housing	Polycarbonate
Environment	Interior
General application	Hospitality, Logistics & Industry
ETIM Class	EC000109
Fixture luminous flux (lm)	1140
Luminaire efficacy (lm/W)	76
LOR (%)	80
Colour temperature (K)	4000
Light colour	Neutral White
Total power consumption (W)	15
Electrical protection	Class I
Control gear type	Electronic
Housing colour	RAL9016
IP rating	IP66
IK rating	IK08
Product EAN number	5410288423005
Included lamp	0002761

### DATA TABLE

#### General data

IPC Code	0042300
Product name	Start Tubular IP66 114 EB 840
Technology	Fluorescent
Housing	Polycarbonate
Environment	Interior
General application	Hospitality, Logistics & Industry
Operating temperature range (°C)	0 to +25
ETIM Class	EC000109

#### Optical data

Fixture luminous flux (lm)	1140
----------------------------	------

## Start Tubular - Electronic

*Start Tubular IP66 114 EB 840*

0042300

Luminaire efficacy (lm/W)	76
LOR (%)	80
Colour temperature (K)	4000
Light colour	Neutral White
Adjustable chromaticity	N
Distribution type	Direct

### Electrical data

Total power consumption (W)	15
Mains voltage (V)	220-240V~
Electrical protection	Class I
Control gear type	Electronic
Transformer required	Yes
Glow Wire Test (°C)	850
Lamp Energy Label (class)	A+
Nominal Frequency (Hz)	50/60Hz

### Physical data

Housing colour	RAL9016
IP rating	IP66
IK rating	IK08
Diffuser finish	Clear
Diffuser material	Polycarbonate
Reflector finish	White
Nominal Product Length (mm)	678
Nominal Product Width (mm)	118
Nominal Product Height (mm)	119
Weight (kg)	1.4

### Packaging


Single packaging type	Carton
Product EAN number	5410288423005
Packaging single length / height (cm)	70.0
Packaging single width (cm)	13.0
Packaging single depth (cm)	13.0
DUN14 (outer)	05410288423005
Units per outer package	1
Packaging outer length / height (cm)	70.0
Packaging outer width (cm)	13.0
Packaging outer depth (cm)	13.0


## PHOTOMETRY

## Start Tubular - Electronic


Start Tubular IP66 114 EB 840  
0042300


**SYLVANIA** 0042300


 This luminaire is compatible with bulbs of the energy classes:




This luminaire is sold with a bulb of the energy class:

874/2012 

 This luminaire is compatible with bulbs of the energy classes:



This luminaire is sold with a bulb of the energy class:

**SYLVANIA** 0042300  874/2012