Start Spot IP65

START SPOT LED DIM IP65 4000K

0053587



Product features

- Integrated dimmable LED IP65 from the front fixed downlight, RAL9016, 580LM, 7W, 4000K, 100 degree beam angle, polycarbonate white body, low profile 41mm recessed depth, 86mm bezel diameter, 65-74mm cutout, frosted lens.

PRODUCT OVERVIEW

IPC Code	0053587
Product name	START SPOT LED DIM IP65 4000K
Technology	LED
Housing	Polycarbonate
Mount	Ceiling recessed
General application	Residential & Consumer,
Certifications	EUNEW008
ETIM Class	EC001744
E-number SE	7470892
Fixture luminous flux (lm)	580
Luminaire efficacy (lm/W)	83
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Beam Angle (°)	100
Glare control	32.9
Photobiological Risk Group	RG0
Total power consumption (W)	7
Electrical protection	Class II
Control gear type	Integral
Dimmable	Yes
LED Flickering Rate	Medium (21% - 40%)
Average life (Nominal) (h)	30000
Housing colour	White
IP rating	IP65/20
IK rating	IK03
Product EAN number	5410288535876
Lamps	No

DATA TABLE

General data

© Feilo Sylvania | Date Printed: 28 Dec 2018

Start Spot IP65

START SPOT LED DIM IP65 4000K

0053587

IPC Code	0053587
Product name	START SPOT LED DIM IP65 4000K
Technology	LED
Housing	Polycarbonate
Mount	Ceiling recessed
General application	Residential & Consumer,
Operating temperature range (°C)	-10 to +40°C
Certifications	EUNEW008
ETIM Class	EC001744
E-number SE	7470892

Optical data

Fixture luminous flux (lm)	580
Luminaire efficacy (lm/W)	83
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Beam Angle (°)	100
Distribution type	Direct
Glare control	32.9
Photobiological Risk Group	RG0

Electrical data

Total power consumption (W)	7
Mains voltage (V)	220-240V~
Lamp power factor	0.8
THD (at 230 V, 50 Hz, full load, at 100% dimming level) xx.x %	30
Electrical protection	Class II
Control gear type	Integral
Dimmable	Yes
Drive current (mA)	70
Inrush Current (A)	8
Inrush Duration (µs)	250
Glow Wire Test (°C)	650
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Medium (21% - 40%)
Max. Luminaires per 10A C Breaker	10
Max. Luminaires per 13A C Breaker	13
Max. Luminaires per 16A C Breaker	14
Max. Luminaires per 20A C Breaker	14

Lifetime data

Lumen maintenance - L70 B50	25000
Average life (Nominal) (h)	30000

Physical data

Housing colour	White

© Feilo Sylvania | Date Printed: 28 Dec 2018

Start Spot IP65

START SPOT LED DIM IP65 4000K


0053587

IP rating	IP65/20
IK rating	IK03
Diffuser finish	Opal
Diffuser material	Acrylic
Nominal Product Length (mm)	86
Nominal Product Width (mm)	86
Nominal Product Height (mm)	41
Nominal Product Diameter (mm)	86
Weight (kg)	0.076
Recessed Depth (mm)	40

Packaging

Single packaging type	Carton
Product EAN number	5410288535876
Packaging single length / height (cm)	9.0
Packaging single width (cm)	7.5
Packaging single depth (cm)	9.0
DUN14 (inner)	25410288535870
Units per inner package	6
Packaging inner length / height (cm)	28.5
Packaging inner width (cm)	9.0
Packaging inner depth (cm)	19.0
DUN14 (outer)	15410288535873
Units per outer package	48
Packaging outer length / height (cm)	38.0
Packaging outer width (cm)	30.0
Packaging outer depth (cm)	40.5

PHOTOMETRY




TECHNICAL DRAWINGS


© Feilo Sylvania | Date Printed: 28 Dec 2018

Start Spot IP65

START SPOT LED DIM IP65 4000K

0053587






© Feilo Sylvania | Date Printed: 28 Dec 2018

Start Spot IP65

START SPOT LED DIM IP65 4000K

0053587



© Feilo Sylvania | Date Printed: 28 Dec 2018