

Start Spot IP65

START SPOT LED DIM IP65 6500K

0053588



Product features

- Integrated dimmable LED IP65 from the front fixed downlight, RAL9016, 590LM, 7W, 6500K, 100 degree beam angle, polycarbonate white body, low profile 41mm recessed depth, 86mm bezel diameter, 65-74mm cutout, frosted lens.



PRODUCT OVERVIEW

IPC Code	0053588
Product name	START SPOT LED DIM IP65 6500K
Technology	LED
Housing	Polycarbonate
Mount	Ceiling recessed
General application	Residential & Consumer
Certifications	EUNEW008
ETIM Class	EC001744
Fixture luminous flux (lm)	590
Luminaire efficacy (lm/W)	84
Colour temperature (K)	6500
Light colour	Daylight
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Beam Angle (°)	100
Glare control	33.5
Photobiological Risk Group	RG0
Total power consumption (W)	7
Electrical protection	Class II
Control gear type	Integral
Dimmable	Yes
LED Flickering Rate	Medium (21% - 40%)
Average life (Nominal) (h)	30000
Housing colour	White
IP rating	IP65/20
IK rating	IK03
Product EAN number	5410288535883
Lamps	No

DATA TABLE

General data

IPC Code	0053588
----------	---------

Start Spot IP65

START SPOT LED DIM IP65 6500K

0053588

Product name	START SPOT LED DIM IP65 6500K
Technology	LED
Housing	Polycarbonate
Mount	Ceiling recessed
General application	Residential & Consumer
Operating temperature range (°C)	-10 to +40°C
Certifications	EUNEW008
ETIM Class	EC001744

Optical data

Fixture luminous flux (lm)	590
Luminaire efficacy (lm/W)	84
Colour temperature (K)	6500
Light colour	Daylight
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Beam Angle (°)	100
Distribution type	Direct
Glare control	33.5
Photobiological Risk Group	RG0

Electrical data

Total power consumption (W)	7
Mains voltage (V)	220-240V~
Lamp power factor	0.8
THD (at 230 V, 50 Hz, full load, at 100% dimming level) xx.x %	30
Electrical protection	Class II
Control gear type	Integral
Dimmable	Yes
Drive current (mA)	70
Inrush Current (A)	8
Inrush Duration (µs)	250
Glow Wire Test (°C)	650
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Medium (21% - 40%)
Max. Luminaires per 10A C Breaker	10
Max. Luminaires per 13A C Breaker	13
Max. Luminaires per 16A C Breaker	14
Max. Luminaires per 20A C Breaker	14

Lifetime data

Lumen maintenance - L70 B50	25000
Average life (Nominal) (h)	30000

Physical data

Housing colour	White
IP rating	IP65/20
IK rating	IK03

Start Spot IP65

START SPOT LED DIM IP65 6500K


0053588

Diffuser finish	Opal
Diffuser material	Acrylic
Nominal Product Length (mm)	86
Nominal Product Width (mm)	86
Nominal Product Height (mm)	41
Nominal Product Diameter (mm)	86
Weight (kg)	0.076
Recessed Depth (mm)	40

Packaging

Single packaging type	Carton
Product EAN number	5410288535883
Packaging single length / height (cm)	9.0
Packaging single width (cm)	7.5
Packaging single depth (cm)	9.0
DUN14 (inner)	25410288535887
Units per inner package	6
Packaging inner length / height (cm)	28.5
Packaging inner width (cm)	9.0
Packaging inner depth (cm)	19.0
DUN14 (outer)	15410288535880
Units per outer package	48
Packaging outer length / height (cm)	38.0
Packaging outer width (cm)	30.0
Packaging outer depth (cm)	40.5

PHOTOMETRY



0.5	1.13	E(0°) E(C0)	960 141
1.0	2.25	E(0°) E(C0)	241 36
1.5	3.38	E(0°) E(C0)	107 16
2.0	4.51	E(0°) E(C0)	60 9
2.5	5.63	E(0°) E(C0)	39 6
3.0	6.76	E(0°) E(C0)	27 4


Distance [m] Cone diameter [m]
C0 - C180 (Half beam angle: 96.8°) Illuminance [lx]

TECHNICAL DRAWINGS

Start Spot IP65

START SPOT LED DIM IP65 6500K


0053588



SYLVANIA 0053588



This luminaire contains built in LED lamps.



A++
A+
A
B
C
D
E

} LED

The lamps cannot be changed in the luminaire.

874/2012 

Start Spot IP65

START SPOT LED DIM IP65 6500K

0053588

