

Start Spot IP65


START SPOT LED IP65 SUNDIM

0053589



Product features

- Integrated dimmable to warm LED IP65 from the front fixed downlight, RAL9016, 480LM, 6.5W, 3000K to 2200K, 100 degree beam angle, polycarbonate white body, low profile 41mm recessed depth, 86mm bezel diameter, 65-74mm cutout, frosted lens.



PRODUCT OVERVIEW

IPC Code	0053589
Product name	START SPOT LED IP65 SUNDIM
Technology	LED
Housing	Polycarbonate
Mount	Ceiling recessed
General application	Residential & Consumer,
Certifications	EUNEW008
ETIM Class	EC001744
E-number SE	7470893
Fixture luminous flux (lm)	480
Luminaire efficacy (lm/W)	74
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Beam Angle (°)	100
Glare control	32
Photobiological Risk Group	RG0
Total power consumption (W)	6.5
Electrical protection	Class II
Control gear type	Integral
Dimmable	Yes
LED Flickering Rate	Medium (21% - 40%)
Average life (Nominal) (h)	30000
Housing colour	White
IP rating	IP65/20
IK rating	IK03
Product EAN number	5410288535890
Lamps	No

Start Spot IP65

START SPOT LED IP65 SUNDIM

0053589

DATA TABLE

General data

IPC Code	0053589
Product name	START SPOT LED IP65 SUNDIM
Technology	LED
Housing	Polycarbonate
Mount	Ceiling recessed
General application	Residential & Consumer,
Operating temperature range (°C)	-10 to +40°C
Certifications	EUNEW008
ETIM Class	EC001744
E-number SE	7470893

Optical data

Fixture luminous flux (lm)	480
Luminaire efficacy (lm/W)	74
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Beam Angle (°)	100
Distribution type	Direct
Glare control	32
Photobiological Risk Group	RG0

Electrical data

Total power consumption (W)	6.5
Mains voltage (V)	220-240V~
Lamp power factor	0.5
Electrical protection	Class II
Control gear type	Integral
Dimmable	Yes
Drive current (mA)	115
Inrush Current (A)	8
Inrush Duration (µs)	320
Glow Wire Test (°C)	650
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Medium (21% - 40%)
Max. Luminaires per 10A C Breaker	8
Max. Luminaires per 13A C Breaker	10
Max. Luminaires per 16A C Breaker	12
Max. Luminaires per 20A C Breaker	13

Lifetime data

Lumen maintenance - L70 B50	25000
Average life (Nominal) (h)	30000

Start Spot IP65

START SPOT LED IP65 SUNDIM

0053589



Physical data

Housing colour	White
IP rating	IP65/20
IK rating	IK03
Diffuser finish	Opal
Diffuser material	Acrylic
Nominal Product Length (mm)	86
Nominal Product Width (mm)	86
Nominal Product Height (mm)	41
Nominal Product Diameter (mm)	86
Weight (kg)	0.076
Recessed Depth (mm)	40

Packaging

Single packaging type	Carton
Product EAN number	5410288535890
Packaging single length / height (cm)	9.0
Packaging single width (cm)	7.5
Packaging single depth (cm)	9.0
DUN14 (inner)	25410288535894
Units per inner package	6
Packaging inner length / height (cm)	28.5
Packaging inner width (cm)	9.0
Packaging inner depth (cm)	19.0
DUN14 (outer)	15410288535897
Units per outer package	48
Packaging outer length / height (cm)	38.0
Packaging outer width (cm)	30.0
Packaging outer depth (cm)	40.5

PHOTOMETRY




TECHNICAL DRAWINGS

Start Spot IP65

START SPOT LED IP65 SUNDIM


0053589



SYLVANIA 0053589



This luminaire contains built in LED lamps.



**L
E
D**

The lamps cannot be changed in the luminaire.

874/2012 

Start Spot IP65

START SPOT LED IP65 SUNDIM

0053589

