



PROPERTY SHEET	
Product	TETA Smart Glass® Film
Model	TT120LU01
Color	Paper White
Thickness	0,4 mm ±0,02
Dimensions	1200 mm max. width
Operation	Transparent (On State) Opaque (Off State)
Light Transmittance	%82 (On) %2 (Off)
Opacity	%6 (On) %95 (Off)
UV Blocking	%98
IR Blocking	%40 (Off State)
Response Time	On/Off: 50 ms Off/On: 10 ms
Operating Voltage	60 Volts AC
Power Consumption	~7W/m ² (On State)
Driving Current	~100mA/m ²
Frequency	50/60 Hz
Operating Temperature	-30° C / +80° C
Storage Conditions	-10° C / +50° C, <70% Humidity
On/Off Cycle	>3.000.000
Lifetime	>50.000 hours >10 years (room conditions)

HQ:

YILDIZ POSTA CAD. YILDIZ RESIDENCE
NO:24 7/17 GAYRETTEPE BEŞİKTAŞ
İSTANBUL

PRODUCTION FACILITY:

İDOŞB. TACİR SOKAK NO:24/23 AYDINLI
TUZLA İSTANBUL

Ph: +90 (212) 236 00 11

Fax: +90 (212) 272 51 72

E-mail: info@tetacam.com



www.tetacam.com

