Company	S/N	Model	Performance Characteristics
Vulcan Fire Products Trading	1	Vulcan	A Single and a Pair Swinging hollow metal type fire doors. ▪ **Fire rating**: 45, 60, 90, 120 & 180min. ▪ Maximum size: 1345x2936x46mm
	2	Vulcan	Three-sided steel door frames for use as a component in fire door assemblies ▪ **Fire rating**: 45, 60, 90, 120 & 180min. ▪ Maximum size: 2800x2995x150mm§ Maximum size: 2800x2995x150mm
	3	VSD04	Honeycomb filled double leaf single acting steel doorset with vision panel ▪ **Fire rating:** 240min. (integrity)§ **Fire rating:** 240min. (integrity) ▪ Maximum size: 2400x2400x150mm§ Maximum size: 2400x2400x150mm
	3	VSD05	Double leaf fully glazed doorset with side lights and over panel ▪ **Fire rating:** 120min. (integrity)§ **Fire rating:** 120min. (integrity) ▪ Maximum size: 3000x3000x150mm§ Maximum size: 3000x3000x150mm
	4	Vulcan	Non-load bearing fully glazed steel partition ▪ **Fire rating:** 90min. (integrity); 13min.(insulation)§ **Fire rating:** 90min. (integrity); 13min.(insulation) ▪ Maximum size: 3000mm high x unrestricted width§ Maximum size: 3000mm high x unrestricted width
	5	LSASLWD-120	Latched Single Acting Single Leaf Wooden Doorset with Vision Panel ▪ **Fire rating:** 90 & 120min. (integrity and insulation)§ **Fire rating:** 90 & 120min. (integrity and insulation) ▪ Maximum size: 1144x2453x150mm§ Maximum size: 1144x2453x150mm
	6	VWD01	Latched Single Acting Leaf Wooden Doorset ▪ **Fire rating:** 60min. (integrity)§ **Fire rating:** 60min. (integrity) ▪ Maximum size: 1150x2835x150mm§ Maximum size: 1150x2835x150mm
	7	MC-777	Fire Resistant Roller Shutter mounted to masonry wall type constructions. Maximum size: 8000 x 12000mm

Cert. Date
28-Nov-18