

Syl-lighter LED II 240

SYL-LIGHTER II 240 25W WW 1-10V
3031855



Product features

- Ceiling recessed IP44 from the front LED downlight, perfect where limited ceiling void is available with only 65mm product depth and 225mm cutout. Ideal replacement for 2x26W CFL downlights. The polycarbonate diffuser allows for a wider light distribution and increased spacings between luminaires. Loop in loop out connector allows for quick installation. Die-cast aluminium body, 2325LM, 25W, 93lm/W, 3000K, Driver Current: 650mA, CRI80, 74° beam angle, 1-10V dimmable LED driver, IP44 from the front, IK07, 50,000 hrs (L70), (HxW) 65x225mm, 5 step MacAdam ellipse, 0.65kg, RAL9003, Class 2, 220-240V, energy class: A++, A+, A



PRODUCT OVERVIEW

IPC Code	3031855
Product name	SYL-LIGHTER II 240 25W WW 1-10V
Technology	LED
Housing	Aluminium
Mount	Ceiling recessed
Fixture rating	Enclosed
Environment	Interior
General application	Hospitality
Certifications	EUNEW008
ETIM Class	EC001744
E-number FI	4270336
E-number SE	7470960
Fixture luminous flux (lm)	2325
Luminaire efficacy (lm/W)	93
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Consistency (SDCM)	5
Photobiological Risk Group	RG0
Total power consumption (W)	25
Electrical protection	Class II
Control gear type	Dimmable
Control gear mounting	Remote
Dimmable	Yes
Minimum dimming level (%)	1
Average life (Nominal) (h)	50000
Housing colour	White - RAL9003
IP rating	IP44/20
IK rating	IK07
Product EAN number	8711971318552
Lamps	No
Included lamp	INTEGRATED LED

Syl-lighter LED II 240

SYL-LIGHTER II 240 25W WW 1-10V
3031855

DATA TABLE

General data

IPC Code	3031855
Product name	SYL-LIGHTER II 240 25W WW 1-10V
Technology	LED
Housing	Aluminium
Mount	Ceiling recessed
Fixture rating	Enclosed
Environment	Interior
General application	Hospitality
Certifications	EUNEW008
ETIM Class	EC001744
E-number FI	4270336
E-number SE	7470960

Optical data

Fixture luminous flux (lm)	2325
Luminaire efficacy (lm/W)	93
LOR (%)	100
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Consistency (SDCM)	5
Beam angle (Rated) (°)	74
Distribution type	Direct - Symmetrical
Photobiological Risk Group	RG0

Electrical data

Total power consumption (W)	25
Mains voltage (V)	220-240V~
Lamp power factor	0.95
Electrical protection	Class II
Control gear required	Yes
Control gear type	Dimmable
Control gear mounting	Remote
Dimmable	Yes
Minimum dimming level (%)	1
Drive current (mA)	650
Inrush Current (A)	5
Inrush Duration (µs)	50
Glow Wire Test (°C)	650
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 16A B Breaker	50

Lifetime data

Lumen maintenance - L70 B50	50000
Average life (Nominal) (h)	50000

Syl-lighter LED II 240

SYL-LIGHTER II 240 25W WW 1-10V
3031855


Physical data

Housing colour	White - RAL9003
IP rating	IP44/20
IK rating	IK07
Diffuser finish	Opal
Diffuser material	Polycarbonate
Reflector finish	Diffuser
Nominal Product Height (mm)	65
Nominal Product Diameter (mm)	240
Weight (kg)	0.851

Packaging

Single packaging type	Carton
Product EAN number	8711971318552
Packaging single length / height (cm)	27.6
Packaging single width (cm)	27.3
Packaging single depth (cm)	8.1
DUN14 (outer)	18711971318552
Units per outer package	12
Packaging outer length / height (cm)	56.3
Packaging outer width (cm)	56.5
Packaging outer depth (cm)	27.3


PHOTOMETRY



Distance [m]	Cone diameter [m]	E ₀ [lx]	E ₁ [lx]	E ₂ [lx]
0.5	0.79	5135	1284	309
1.0	1.59	1284	309	77
1.5	2.38	571	137	32
2.0	3.17	321	77	15
2.5	3.96	205	49	10
3.0	4.76	143	34	7


Distance [m] Cone diameter [m] Illuminance [lx]
C0 - C180 (Half beam angle: 76.8°)


TECHNICAL DRAWINGS




Syl-lighter LED II 240 SYL-LIGHTER II 240 25W WW 1-10V 3031855


Lumiance 3031855


 This luminaire contains built in LED lamps.

 } LED


The lamps cannot be changed in the luminaire.

874/2012 

 This luminaire contains built in LED lamps.

 } LED

The lamps cannot be changed in the luminaire.

Lumiance 3031855  874/2012