

SylSafe Bay

SylSafe Bay MB C EM3 NM MS

0041735



Product features

- SylSafe Bay MB C EM3 NM MS is a dust and waterproof surface mounted emergency luminaire for industrial applications. Midbay optics for medium ceiling heights. Non-maintained 3hr emergency duration with NiMH rechargeable battery. Recharge period 24 hours. 200lm, 3W, IK03, IP65. Power Factor 0.44. Class II electrical construction.



PRODUCT OVERVIEW

IPC Code	0041735
Product name	SylSafe Bay MB C EM3 NM MS
Technology	LED
Type	LED
Mount	Surface mounted
General application	Office, Hospitality, Retail, Museums & Galleries, Education, Logistics & Industry,
Certifications	EUNEW002
ETIM Class	EC001957
Fixture luminous flux (lm)	200
Luminaire efficacy (lm/W)	67
Colour temperature (K)	5700
CRI (Ra)	75
Photobiological Risk Group	RG1
Luminous flux (emergency) (lm)	200
Total power consumption (W)	3
Electrical protection	Class II
Control gear type	Emergency (3 hour non-maintained)
Average life (Nominal) (h)	35040
Housing colour	White
IP rating	IP65
IK rating	IK03
Product EAN number	5410288417356
Lamps	No
Included lamp	INTEGRATED LED

DATA TABLE

General data

IPC Code	0041735
Product name	SylSafe Bay MB C EM3 NM MS
Technology	LED
Type	LED
Mount	Surface mounted

SylSafe Bay

SylSafe Bay MB C EM3 NM MS

0041735

General application	Office,Hospitality,Retail,Museums & Galleries,Education,Logistics & Industry,
Certifications	EUNEW002
ETIM Class	EC001957

Optical data

Fixture luminous flux (lm)	200
Luminaire efficacy (lm/W)	67
Colour temperature (K)	5700
CRI (Ra)	75
Distribution type	Mid-Bay
Photobiological Risk Group	RG1
Luminous flux (emergency) (lm)	200
Emergency duration (h)	3

Electrical data

Total power consumption (W)	3
Mains voltage (V)	230-240V~
Lamp power factor	0.44
Electrical protection	Class II
Control gear required	Yes
Control gear type	Emergency (3 hour non-maintained)
Drive current (mA)	30
kWh per 1000 hours burning time	3
Nominal Frequency (Hz)	50/60Hz

Lifetime data

Average life (Nominal) (h)	35040
----------------------------	-------

Physical data


Housing colour	White
IP rating	IP65
IK rating	IK03
Nominal Product Length (mm)	197
Nominal Product Width (mm)	197
Nominal Product Height (mm)	53

Packaging


Single packaging type	Mix(80% carton, 20% plastic)
Product EAN number	5410288417356
DUN14 (outer)	05410288417356
Units per outer package	5
Packaging outer length / height (cm)	42.2
Packaging outer width (cm)	25.2
Packaging outer depth (cm)	13.2

PHOTOMETRY

SylSafe Bay
SylSafe Bay MB C EM3 NM MS
0041735



TECHNICAL DRAWINGS



SylSafe Bay

SylSafe Bay MB C EM3 NM MS

0041735

