

Officelyte Classic LED

OFFLYTE CLASSIC LED HO 4K EM

2058061



Product features

- Concord OfficeLyte Classic LED HO 4K EM is a high performance low glare luminaire for offices and education applications. Ceiling recessed 600x600mm. Micro Prismatic optics. White RAL 9010. Emergency 3 hours maintained, 4000K Neutral White LED, CRI >85, chromaticity tolerance of 3-step MacAdam ellipse, lumen package of 3,750lm, total power consumption 51W, efficacy of 74lm/W. Lumen maintenance of L70B50 at 50,000 hours, UGR<19. IK02, IP40, Electrical Protection Class II. Polycarbonate diffuser, Glow Wire test 850°C.



PRODUCT OVERVIEW

IPC Code	2058061
Product name	OFFLYTE CLASSIC LED HO 4K EM
Technology	LED
Housing	Zintec Steel
Mount	Ceiling recessed
General application	Office,Hospitality,Retail,Education,
Certifications	EUNEW001
ETIM Class	EC002892
Fixture luminous flux (lm)	3750 (EM=182)
Luminaire efficacy (lm/W)	139
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Glare control	UGR<19
Photobiological Risk Group	0
Total power consumption (W)	27
Electrical protection	Class II
Control gear type	External
Average life (Nominal) (h)	50000
Housing colour	White RAL 9010
IP rating	IP40
IK rating	IK02
Product EAN number	5025768580613
Lamps	Yes
Included lamp	INTEGRATED LED

DATA TABLE

General data

IPC Code	2058061
Product name	OFFLYTE CLASSIC LED HO 4K EM

Officelyte Classic LED

OFFLYTE CLASSIC LED HO 4K EM

2058061

Technology	LED
Housing	Zintec Steel
Mount	Ceiling recessed
General application	Office,Hospitality,Retail,Education,
Certifications	EUNEW001
ETIM Class	EC002892

Optical data

Fixture luminous flux (lm)	3750 (EM=182)
Luminaire efficacy (lm/W)	139
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Consistency (SDCM)	3
Adjustable chromaticity	N
Distribution type	Direct
Glare control	UGR<19
Photobiological Risk Group	0
Emergency duration (h)	3

Electrical data

Total power consumption (W)	27
Mains voltage (V)	220-240V~
Mains frequency (Hz)	50
Electrical protection	Class II
Control gear type	External
Drive current (mA)	1400
Inrush Current (A)	20
Inrush Duration (µs)	200
Glow Wire Test (°C)	850
Lamp Energy Label (class)	A++
Max. Luminaires per 16A C Breaker	28

Lifetime data

Average life (Nominal) (h)	50000
----------------------------	-------

Physical data

Housing colour	White RAL 9010
IP rating	IP40
IK rating	IK02
Diffuser finish	Satin
Diffuser material	Acrylic
Reflector finish	Micro Prismatic
Nominal Product Length (mm)	595
Nominal Product Width (mm)	595
Nominal Product Height (mm)	95
Weight (kg)	7.7
Recessed Depth (mm)	90

Officelyte Classic LED




OFFLYTE CLASSIC LED HO 4K EM

2058061

Packaging


Single packaging type	Carton
Product EAN number	5025768580613
Packaging single length / height (cm)	62.0
Packaging single width (cm)	62.0
Packaging single depth (cm)	17.0
DUN14 (outer)	05025768580613
Units per outer package	1
Packaging outer length / height (cm)	62.0
Packaging outer width (cm)	62.0
Packaging outer depth (cm)	17.0

PHOTOMETRY



TECHNICAL DRAWINGS

Officelyte Classic LED OFFLYTE CLASSIC LED HO 4K EM 2058061



Concord 2058061



This luminaire is compatible with bulbs of the energy classes:

A++

A+

A

B

C

D

E

}

L

E

D

This luminaire is sold with a bulb of the energy class:

874/2012


Officelyte Classic LED

OFFLYTE CLASSIC LED HO 4K EM
2058061

