

ToLEDo Retro Candle

ToLEDo RT T25 V3 CL 250LM 827 E14 SL

0027243



Product features

- Perfect for decorative and general lighting applications and creates a warm ambiance similar to traditional lamps • ToLEDo Retro T25 lamp is the ideal replacement for incandescent cooker hood lamps. • Same look, size and functionality as incandescent lamps. • Omni-directional light distribution. • A++ energy rating - up to 100 lm/W. • Suitable for replacement of 25W incandescent lamps. • Gives same sparkling light effect as incandescent lamp. • 90% energy saving. • Dimensionally identical to incandescent lamps - fits all fixtures • Environment friendly - no mercury and lower CO2 emissions. • Color temperature - 2700K Homelight



PRODUCT OVERVIEW

IPC Code	0027243
Product name	ToLEDo RT T25 V3 CL 250LM 827 E14 SL
Technology	LED
Watt (Rated) (W)	2
Cap/Base	E14
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Certifications	EUTIE103
ETIM Class	EC001959
E-number FI	4740588
Luminous flux (lm)	250
Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Colour Consistency (SDCM)	6
Beam Angle (°)	300
Wattage (W)	2
Product Voltage (V)	230
Average life (Nominal) (h)	15000
Product EAN number	5410288272436

DATA TABLE

General data

IPC Code	0027243
Product name	ToLEDo RT T25 V3 CL 250LM 827 E14 SL
Technology	LED
Watt (Rated) (W)	2
Cap/Base	E14
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Operating temperature rated (°C)	25
Certifications	EUTIE103

ToLEDo Retro Candle

ToLEDo RT T25 V3 CL 250LM 827 E14 SL

0027243

ETIM Class	EC001959
E-number FI	4740588

Optical data

Luminous flux (lm)	250
Luminous flux (Rated) (lm)	250
Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Colour Variation Initial (SDCM)	6
Colour Consistency (SDCM)	6
Beam Angle (°)	300
Beam angle (Rated) (°)	300
Lumen maintenance at end of nominal life (%)	70

Electrical data

Wattage (W)	2
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	1
Product Voltage (V)	230
Lamp power factor	0.5
No. Of switching cycles before premature failures	50000
Lamp Energy Label (class)	A++
kWh per 1000 hours burning time	2
Nominal Frequency (Hz)	50/60Hz

Lifetime data

Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

Physical data

Nominal Product Length (mm)	90
Nominal Product Diameter (mm)	25
Weight (kg)	0.008

Packaging

Single packaging type	Carton
Product EAN number	5410288272436
Packaging single length / height (cm)	2.5
Packaging single width (cm)	2.5
Packaging single depth (cm)	8.7
DUN14 (inner)	25410288272430
Units per inner package	6
Packaging inner length / height (cm)	8.6
Packaging inner width (cm)	5.8
Packaging inner depth (cm)	10.0
DUN14 (outer)	15410288272433

ToLEDo Retro Candle

ToLEDo RT T25 V3 CL 250LM 827 E14 SL

0027243

Units per outer package	60
Packaging outer length / height (cm)	33.2
Packaging outer width (cm)	20.1
Packaging outer depth (cm)	13.7

Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

