

## DESCRIPTION

- Amplified sounder (for outdoor) for bells, melodies, voice calls and SEP\* alarm.
- 3 operating modes:
  - Broadcast of melodies stored in the product. Control by Sigma master clock (the Ethernet network) or by manual command from the control box (ex: SEP alarm).
  - Voice calls: from microphone or sent from the computer.
  - Broadcast of streaming audio and/or music from the computer.
- The adjustment of the sound level is accomplished via the embedded web server (for all broadcasts).

\*SEP: Safety Emergency Procedures.



See the product page  
>> [www.bodet-time.com](http://www.bodet-time.com) <<






## NORMS

- CEM 2004/108/CEE Directive and Low Voltage Directive 2006/95/CEE.
- EN 60950: Safety of information technology equipment.
- EN 55022: Radio disturbance of information technology equipment.
- EN 55024: Immunity of information technology equipment.

## VERSIONS

- **2 versions**..... 1 horn loudspeaker + controller.  
2 horn loudspeakers + controller.

## TECHNICAL FEATURES

- **Test**..... 1 button.
- **Power supply indicator**..... - Led ON (green) = device powered on:   
- Led OFF = no power: 
- **Network indicator**..... - Led flashing green quickly = connection to the network in progress:   
- Led flashing green slowly = device connected to the network:   
- Led flashing red slowly = loss of network connection or failure to connect to the network: 
- **Audio files format**..... MP3.
- **Adjustable sound level**..... 110 db maximum (1 meter).

## MECHANICAL FEATURES




- **Protection Index**..... Loudspeaker: IP 54. Controller: IP 54, IK 08.
- **Operating temperature range**..... -30° to +85°C.
- **Weight**..... Loudspeaker: 1.7 kg. Controller: 0.6 kg.
- **Dimensions**..... Loudspeaker: H254 x Ø 203 mm. Controller: H97.5 x L250 x D97.5 mm.
- **Mounting**..... Wall.
- **Distance between controller and loudspeaker** 5 meters (max length: 40m).

## ELECTRICAL FEATURES

- **Power supply**..... 110-230VAC ±10%, 50/60 Hz.
- **Consumption**..... 8 W (1 loudspeaker), 15 W (2 loudspeakers).

## REFERENCES

- **907 730**..... Harmonys outdoor 100-240VAC 1 loudspeaker
- **907 731**..... Harmonys outdoor 100-240VAC 2H loudspeakers



Dimensions in mm

